

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 457100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 3 only, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 556)

-----  
Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for gr. sec. cor., marked ¼ S on N. face, from which  
A Fir 40" dia., bears N.30°W., 23 lks. dist. mkd. ¼ S BT.  
A Fir 36" dia., bears S.51°E., 11 lks. dist. mkd. ¼ S BT.

Fd. and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 572)

BLM Resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, Group #1159, Surveyed Aug. 1983/May 1984 - (DCSO records Vol. 47 Page(s) 18034-35)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

T 20 S R 7 W  
-----  
¼ S 3  
T 21 S R 7 W  
1984

from which

A Fir 7" dia., bears S.56°E., 66 lks. mkd. ¼ S3 BT.  
A Hemlock 5" dia., bears S.72°W., 29 lks. mkd. ¼ S3 BT.

Fd. Ok by Craig Wanless - 9/2005 - M148-50