

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 593)

Set sandstone, 18x12x8" 12" in the ground for the 1/4 sec. cor. marked 1/4 on W face; from which

A fir, 24" dia., bears N.25°W., 42 lks., mkd: 1/4 S BT.
A maple, 5" dia., bears S.10°E., 72 lks., mkd: 1/4 S BT.

Wilford N. Haines - Feb. 1965 - C.S. File 51/309-1

Found - Old cutting lines East & South
Decomposed sandstone (no marks)
Stub of Fir S.25°W., 42 lks.

Set - 1"x1"x36" "T" iron by stone
No new BTs

By rough measurement, this point is 2622.0 ft. S. of corner to 26 - 27 - 34 - 35

BLM Dependent resurvey by Wayne Rogers & Lance J. Bishop, Cadastral Surveyor, under Group #1159, surveyed Aug.1983/ May 1984 - (DCSO records Vol. 47 Page 18040)

Point for 1/4 sec. cor. of secs. 34 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T20S R7W

1/4
S 34 | S35

1984

from which

A fir, 5" dia., bears S.61 1/2°E., 10 lks., mkd: X BT.

A fir, 6" dia., bears S.67 1/2°W., 36 lks., mkd: 1/4 S34 BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1502, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19091)

The 1/4 sec. cor. of secs. 34 & 35, monumented with an aluminum post, 2 1/2" diam., firmly set, projecting 2" above ground, with aluminum cap mkd.

T20S R7W

1/4
S34 | S35

1984

from which bearing trees mkd. by Rogers and Bishop

A fir, 7" dia., bears S.61 1/2°E., 10 lks., with healed, double blaze.

A fir 8" dia. bears S.67 1/2°W. 36 lks. w/healed double blaze

continued next page

TOWNSHIP 20 RANGE 7 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Craig Wanless - For: Seneca Jones Tmbr Co. - 9/2005 - M148-50 ----- Found - 2½" alum. pipe with USBLM alum cap dated 1984 0.2' above grade. 7" Fir S.61½°E., 6.2 ft. with healed blaze, rec. S.61½°E., 10 lks - 1984 BLM BT 9" Fir S.67½°W., 23.7 ft. with healed blaze, rec. S.67½°W., 36 lks. - 1984 BLM BT New - 10" Fir, N.85½°E., 21.6 ft. to steel spike at side center scribed "¼ S35 BT" 12" Fir, S.8½°W., 17.2 ft. to steel spike at side center scribed "¼ S34 BT"</p>
<p>Fd. as per M148-50 by D. Edwards, 10/2013 - C.S. 65/079-16</p>