

PRIMARY CORNER DESCRIPTION Witness Corner 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 596)

This point being in the bed of Haney Creek, an impracticable place to set a cor., I mark an Alder, 8" dia, bears W., 27 lks., marked ¼ S WC on E side for witness cor. to ¼ sec. cor.; from which (witness cor.)

An alder, 10" dia., bears S.80°E., 44 lks., mkd: ¼S BT WC.

An alder, 14" dia., bears N.70°W., 8 lks., mkd: ¼S BT WC.

Wilford N. Haines - For: Woolley Logging - 11/17/1967 - M35-3

Found - Alder stub for W. Corner of sec. 22

Set - 5/8" steel rod 27 lks. East of W corner on gravel bar in creek for ¼ corner

20" Alder N.64°E., 26.9 ft.

30" Maple S.82°W., 72.0 ft.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1502, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19080)

From the ¼ sec. cor. of secs. 22 & 23, perpetuated & recorded by Haines, in 1967, from original evidence no longer in existence; monumented with an iron rod, 5/8" diam., firmly set, projecting 8" above gravel bar in Haney Creek, from which the bearing trees mkd. by Haines:

An alder, 27" dia., bears N.83°E., 41 lks., with scribe marks ¼ S23 BT visible on bark blaze.

A maple, 39" dia., bears S.82°W., 109 lks., with scribe marks ¼ S22 BT visible on opened, double blaze.

and a reference monument of which I have no record

An iron rod, 5/8 in. dia., firmly set, projecting 6" above ground, bears N.88°15'E., 0.265 chs.

and a new reference monument

A stainless steel post, 28" long, 2½" dia., set 24" in the ground for a reference monument, bears S. 30° W., 37.9 lks., with brass cap mkd. RM ¼ S22 25 FT 1989 and an arrow pointing to the corner.