

PRIMARY CORNER DESCRIPTION N 1/16 Cor. Secs. 22 & 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Wilford N. Haines - For: Woolley Logging - 11/17/1967 - M35-3

Set - 5/8" steel rod
24" alder, S.16°E., 9.0'
24" alder, N.1°W., 25.4'

Douglas Co. Surveyors Office - Stephen J. Flause - Terrie Plouff - Karen Mosley - May 14, 1981 - C.S. File 61/24-20

Found - A 5/8" I.R. as set by Haines is firmly set & protrudes 10" above the ground.
A 24" Alder now a fallen 26" DBH Alder bears S.16°E., 9.0 ft. Tree has fallen on blaze, no scribing is visible.
A 24" Alder now a 28" DBH Alder bears N.3°W., 25.4 ft. (rec. N.1°W., 25.4 ft.) and is bark scribed 1/16 S22 BT.

These trees from Haines survey.
Also an unrecorded bearing tree, an Alder, 11: DBH bears S.1°W., 20.2 ft. and is unmarked except for a BLM bearing tree tag.

Set - Haines monument is accepted as found.
New BT - The unrecorded 11" DBH Alder BT (as noted above) is scribed 1/16 S22 CS BT & new DCSO BT tags are added to all BTs fd.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1502, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19080-1)

The N 1/16 sec. cor. of secs. 22 & 23, established & recorded by Haines, in 1967, further perpetuated & recorded by Flause, in 1981, and is accepted as the corner; monumented with an iron rod, 5/8" diam., loosely set, projecting 6" above ground, from which a bearing tree mkd. by Haines:

An alder, 29" dia., bears N.2°W., 39 lks., with scribe marks 1/16 S22 BT visible on bark blaze.
and a bearing tree mkd. by Flause

An alder, 14" dia., bears S.1°W., 32 lks., with scribe marks 1/16 S22 CS BT visible on bark blaze.
and a new reference monument

A stainless steel post, 28" long, 2½" diam., set 24" in the ground for a reference monument, bears N.85°E., 60.6 lks., with brass cap mkd. RM N 1/16 S23 40 FT 1990 and an arrow pointing to the corner.

The corner is located at the top of an undercut creek bank.