

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 596-7)

Set sandstone, 16x8x4" 12" in ground, for cor. to secs. 14, 15, 22, & 23, marked with 3 notches on S & 2 notches on E edges; from which

- A V. Maple, 6" dia., bears N.75°E., 30 lks., mkd: T20S R7W S14 BT.
- A V. Maple, 7" dia., bears S.85°E., 22 lks., mkd: T20S R7W S23 BT.
- A Willow 4" dia. bears S.39°W. 20 lks. mkd: T20S R7W S22BT
- A V. Maple, 4" dia., bears N.5°W., 24 lks., mkd: T20S R7W S15 BT.

Wilford N. Haines - For: Woolley Logging - 11/17/1967 - M35-3

- Found - Rock with "X"
Set - 5/8" Steel rod alongside
24" Alder S.72°E., 31.8 ft.
28" Fir N.83°E., 40.5 ft.
10" Cedar N.33°W., 42.7 ft.
16" Fir S.2°W., 66.0 ft.

BLM dependent resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors under Group #913, surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16113)

The cor. of secs. 14, 15, 22, & 23, perpetuated & recorded by Haines in 1967, monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, with the orig. sandstone, 16x8x4" firmly set 16" below surface of the ground, alongside iron rod, mkd. X on top, with 3 notches on S & 2 notches on E edges, from which BTs mkd. by Haines:

- A fir, 22" dia., bears N.83°E., 61½ lks. with healed blaze
- An Alder, 24" dia., bears S.72°E., 48½ lks., with scribe marks T20S R7W S23 BT visible on bark.
- A Fir, 18" dia., bears S.2°W., 100 lks. with healed blaze.
- A Cedar, 14" dia. bears N.33°W., 65 lks. with healed blaze

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T20S R7W
S15 S14
S22 S23

1977

Deposit corner stone, reset iron rod, & set a 5 ft. steel fence post alongside iron post.

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor,
under Group #1502, surveyed Aug.1989/April 1991 - (DCSO
records Vol. 50 Page(s) 19081-2)

The cor. of secs. 14, 15, 22, & 23, monumented with an iron
post, 2½" diam., firmly set, projecting 2" above ground, with
brass cap mkd.

T20S R7W
S15 S14
S22 S23
1977

from which the remains of the bearing trees mkd. by Haines,
in 1967

A fir snag, 22" dia., bears N.83°E., 61½ lks., with healed
double blaze.

An alder, 25" dia., bears S.72°E., 48½ lks., with scribe
marks T20S R7W S23 BT visible on bark blaze.

A fir, 23" dia., bears S.2°W., 100 lks., with healed
double blaze.

A cedar, 19" dia., bears N.33°W., 65 lks., with healed
double blaze.

and a new bearing tree

A maple, 12" dia., bears N.55°E., 82 lks., mkd. T20S R7W
S14 BT.