

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 598)

-----  
Set sandstone, 20x14x4" 15" in the ground for the 1/4 sec. cor. marked 1/4 on W face; from which

A cedar, 48" dia., bears N.80°E., 80 lks., mkd: 1/4 S BT.

A fir, 36" dia., bears N.48°W., 20 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Harvey E. Wofford & Lester E. Fischer, Cadastral Surveyors under Group #913, surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16114)

-----  
Point for 1/4 sec. cor. of secs. 13 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap marked:

T20S R7W  
1/4  
S 15|S 14  
1977

from which

A fir, 25" dia., bears S.70°E., 7 lks., mkd: 1/4 S14 BT.

A fir, 30" dia., bears S.59 1/2°W., 97 lks., mkd: 1/4 S15 BT.

Set a 5 ft. steel fence post alongside iron post.

Fd. & used on BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1502, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19086)