

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 555)

-----  
Set post 6" dia., 4 ft. long, with marked stone, 12" in ground, for closing cor. to secs. 2 & 3, marked T20S R7W S35 on the N.; R7W S2 on SE.; T21S S3 on SW.; faces, with 2 notches on the E. and 4 on the W. edges; from which

A Fir 36" dia., bears N.15°E., 31 lks. dist. mkd. T20S R7W S35 BT.

A Fir 30" dia., bears S.81°E., 5 lks. dist. mkd. T21S R7W S2 BT.

A Fir 20" dia., bears S.65°W., 37 lks. dist. mkd. T21S R7W S3 BT.

Fd. and used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 571)

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1502, surveyed Aug. 1989/Apr. 1991 - (DCSO records Vol. 50 Page(s) 19071)

-----  
Point for the cor. of secs. 2 and 3 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T20S R7W  
S3 S2  
T21S R7W  
1990

from which

A fir, 10 ins. diam., bears S. 14° E., 13½ lks. dist., mkd. T21S R7W S2 BT.

A fir, 8 ins. diam., bears S. 74° W., 21 lks. dist., mkd. T21S R7W S3 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located at the edge of a landing with a graveled road, 15 lks. wide, bears S. 15° E.