

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 571)

Set post 4 ft. long, 4" sq., 2 ft. in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which
 A Fir 20" dia., bears N.33°E., 7 lks. dist. mkd. ¼ S BT.
 A Fir 24" dia., bears S.24°E., 10 lks. dist. mkd. ¼ S BT.
Situating at head of spur, course N.

Wilford N. Haines, #239 - Feb. 1965 - C.S. File 51/309-1

Found - 20" Fir, N.33°E., 7 lks., now burned stub, good scribe.
 24" Fir, S.24°E., 10 lks., now windfall, scribe still in stub.
Set 1" x 1" x 36" "T" iron.
New BTs- 48" Fir N.73°W., 33.5 ft.
 44" Fir N.48½°E., 37.5 ft.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1502, surveyed Aug. 1989/Apr. 1991 - (DCSO records Vol. 50 Page(s) 19070-71)

Point for the ¼ sec. cor. of sec. 35 only, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

T20S R7W
 ¼ S35

T21S R7W
 1990

from which

 A fir, 6 ins. diam., bears N. 77° E., 62 lks. dist., mkd. ¼ S35 BT.

 A fir, 8 ins. diam., bears N. 9° W., 45 lks. dist., mkd. ¼ S35 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.