TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 594)

Set post, 4 ft. long, 4" in the ground for the ¼ sec. cor. marked ¼ on N face; from which
A cedar, 24" dia., bears S.30°W., 15 lks., mkd: ¼ S BT.
An ash, 20" dia., bears N.52°E., 54 lks., mkd: ¼ S BT.

Wilford N. Haines - 11/17/1967 - C.S. File 51/309-5

Found - 24" now 48" cedar S.30°W., 15 lks.
Set - 5/8" x 48" steel rod for ¼ corner.
Rescribed -
48" cedar S.30°W., 15 lks.
Scribed- 48" maple N.22°W., 42.4 ft.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1502, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19077-8)

The ¼ sec. cor. of secs. 26 & 35, perpetuated & recorded by Haines, in 1967, monumented with an iron rod, 5/8" dia., firmly set, projecting 16" above ground, from which the remaining original bearing tree:
A cedar, 46" dia., bears S.30°W., 15 lks., with weathered blaze.
and the remains of a bearing tree mkd. by Haines
A maple snag, 48" dia., bears N.22°W., 65 lks., with healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd. T20S R7W ¼ S 26 / S 35 1990
from which a new bearing tree
An ash, 13" dia., bears N. 69° E., 67 lks., mkd. ¼ S26 BT.
Deposit a white "DEEP-1" magnetic marker at the base and the iron rod alongside the stainless steel post.

Fd. BC & 3 BTs 1/1991 L Roberts C.S. 63/129-9 - Set 72" alum post with land monument survey sign bolted to beside BC.

Fd. Ok by D. Edwards 6/1998 - M130-2
Fd. as per 1990 BLM, by D. Edwards, 10/2013 - C.S. 65/079-16