

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 596)

A sandstone in place, 6x4x1 ft. above the ground, marked with cross (x) at exact point for the ¼ sec. cor. marked ¼ on N face; from which

A fir, 14" dia., bears S.88°E., 69 lks., mkd: ¼ S BT.
A maple, 4" dia., bears N.1°E., 52 lks., mkd: ¼ S BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1502, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19078)

Point for the ¼ sec. cor. of secs. 23 & 26, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd. T20S R7W

¼ $\frac{S\ 23}{S\ 26}$
1989

from which

A fir, 17" dia., bears S.66°W., 18 lks., mkd. ¼ S26 BT.
A fir, 15" dia., bears N.55°W., 74 lks., mkd. ¼ S23 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Fd. BC & 2 BTs 1/1991 L Roberts C.S. 63/129-9 - Set 72" alum post with land monument survey sign bolted to beside BC.

Fd. Ok by D. Edwards 6/1998 M130-2

Fd. Ok by R. Rice 9/2011 C.S. File 65/74-16