

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 597)

Set fir post, 4 ft. long, 4" sq. 24" in the ground, for 1/4 sec. cor., mkd. 1/4 S on N face; from which

A fir, 36" dia., bears S.5°E., 28 lks., mkd: 1/4 S BT.

A fir, 24" dia., bears N.21 1/2°E., 30 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1502, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19082-3)

Point for the 1/4 sec. cor. of secs. 14 & 23, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd. T20S R7W

1/4 S 14
S 23
1989

from which

A fir, 28" dia., bears N.46°E., 57 lks., mkd. 1/4 S14 BT.

A fir, 83" dia., bears S.40°E., 40 lks., mkd. 1/4 S23 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.