

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 557100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 555)

A Vine Maple 5" dia., for ¼ sec. cor., marked ¼ S on N. face;
from which

A Fir 40" dia., bears North, 8 lks. dist. mkd. ¼ S BT.

A Fir 48" dia., bears S.45°E., 2 lks. dist. mkd. ¼ S BT.

Fd. and Used in GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 571)

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1502, surveyed Aug. 1989/Apr. 1991 - (DCSO records Vol. 50 Page(s) 19070)

Point for the ¼ sec. cor. of sec. 2 only, T. 21 S., R. 7 W.,
at proportionate distance; there is no remaining evidence of
the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam.,
24 ins. in the ground, with brass cap mkd.

T20S R7W

¼ S2

T21S R7W

1990

from which

A fir, 7 ins. diam., bears S. 52½° E., 18 lks. dist.,
mkd. ¼ S2 BT.

A fir, 6 ins. diam., bears S. 65° W., 8 lks. dist., mkd.
X BT.

Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.