

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 570)

Set post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 35 & 36, marked T20S R7W on N.; S36 on E.; S35 on W. faces, with 1 notch on E. and 5 notches on W. faces; from which

A Fir 30" dia., bears N.6°W., 45 lks. dist. mkd. T20S R7W S35 BT.

A Fir 9" dia., bears N.75°E., 58 lks. dist. mkd. T20S R7W S36 BT.

A Fir 8" dia., bears S.46°E., 38 lks. dist. mkd. T20S R7W S35 & 36 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - and crew - May 1962 - C.S. File 49/20-13

Found - Haines "T" iron at corner.

Fir now 60", N.6°W., 29.7 ft., previously cut open. Good scribing "35" visible on old face. Haines rescribed this tree (in bark) "T20S R7W S35 BT".
28" Fir, N.32°W., 68.2 ft. scribed by Haines, in wood, "T20S R7W S35 BT".

Both trees have Haines' metal disc nailed to face.

New BT - 17" Madrone N.50°E., 51.3 ft. mkd. T20S R7W S36 CS BT.

Cor. lies on top of spur running N.35°W. about 4 chs. W. of top of ridge NE. & SW.

No trace found of orig. NE. or SE. BTs.

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1502, surveyed Aug. 1989/Apro. 1991 - (DCSO records Vol. 50 Page(s) 19069-70)

The Cor. of secs. 35 and 36 only, perpetuated by Wilford N. Haines, Registered Land Surveyor No. 239, year unknown, further perpetuated and recorded by Godfrey, Deputy County Surveyor, in 1962, determined at record bearing and distance from the remains of an original bearing tree:

A sawed fir stump, 50 ins. diam., bears N. 6° W., 45 lks. dist., with scribe marks 7W S visible on opened blaze. and the remains of a bearing tree mkd. by Haines

A sawed fir stump, 34 ins. diam., bears N. 33° W., 104 lks. dist., no marks visible.

and a bearing tree mkd. by Godfrey

A madrone, 19 ins. diam., bears N. 51° E., 78 lks. dist., no marks visible. (Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Set a stainless steel post, 28 ins. long, 2½ ins. diam.,
26 ins. in the ground, with brass cap mkd.

T20S R7W
S35 | S36

S2

T21S R7W
1990

from which new bearing trees

A fir, 4 ins. diam., bears N. 59° E., 47 lks. dist., mkd.
X BT.

A fir, 6 ins. diam., bears N. 67° W., 10 lks. dist., mkd.
T20S R7W S35 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.

The corner is located in the cutbank of a graveled road, 20
lks. wide, bears N. 60° W. and S. 60° E.

From this point, the Bureau of Land Management Geodetic
Control Station No. EC 41050, at latitude 43° 46' 57.245" N.,
longitude 123° 29' 25.276" W. (NAD 1927), determined by the
NAVSTAR Global Positioning System, bears N. 30° 19' 00" W.,
10.822 chs. dist., monumented with an aluminum cap, 2½ ins.
diam., firmly set flush with the ground, in a gravel filled
perforated pipe, 4 ins. diam., with top mkd. EC 41050 GPS
1990.

Harvey Christensen, survey for Seneca Jones Timber Co.
Sept. 1998 - M130-35

Found - 1990 2½" BLM Brass cap in cut bank of road.

- 8" D.Fir, N.59°E., 31.0 ft. healed face.

- 10" D.Fir, N.67°W., 6.6 ft. healed face.

Set 5 ft. steel post 1 foot East.

Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-48

Found - 1990 BLM 2½" brass cap on iron pipe

20" D.Fir, N.67°W., 6.6 ft "healed face"

10" D.Fir snag, N.59°E., 31 ft "healed face"

45" D.Fir stump, N.9°W., 30.5 ft (record N.6°W., 45
29.7 ft)

No record found -

22" D.Fir, S.5°W., 38.8 ft