

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias	Description

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 587)

Set sandstone, 30x20x10" 24" in the ground for the 1/4 sec. cor. marked 1/4 on W face; from which

A Fir, 54" dia., bears S.5°E., 10 lks., mkd: 1/4 S BT.

A Fir, 48" dia., bears N.8°W., 120 lks., mkd: 1/4 S BT.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor 1502, under Group #1392, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19072-3)

The 1/4 sec. cor. of secs. 35 & 36, perpetuated but not recorded by Haines, year unknown, monumented with the original stone, 30x20x10", loosely set, with 1/4 S visible on W. face (alongside of which is a "T" shaped iron rod, 1" dia., firmly set, projecting 24" above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE), from which the remains of the original bearing trees:

A sawed fir stump, 65" dia., bears S.5°E., 10 lks., with scribe marks 1/4 visible on opened blaze.

A sawed fir stump, 74" dia., bears N.8°W., 114 lks., no marks visible. (Record, 120 lks.)

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.

T20S R7W
S35 | S36
1990

from which new bearing trees

A maple, 6" dia., bears N. 45° E., 12 lks., mkd. 1/4 S36 BT.

A fir, 8" dia., bears S. 77° W., 26 lks., mkd. 1/4 S35 BT.

Deposit a white "DEEP-1" magnetic marker and T iron at the base and the original stone alongside the stainless steel post.

Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-48

Found - 1990 BLM 2 1/2" brass cap on iron pipe

1990 BTs not found

New BTs- Face blazed only

10" Big leaf maple, S.5°W., 11.5 ft.

21" D.Fir, West, 49.2 ft.