

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 587)

Set sandstone, 24x10x10" 18" in the ground, for cor. to secs. 25, 26, 35, & 36, with 1 notch on S & E edges; from which
A Fir, 12" dia. bears N.54°E., 6 lks. mkd: T20S R7W S25 BT
A Fir, 8" dia. bears S.39°E., 7 lks. mkd: T20S R7W S36 BT.
A Fir, 14" dia. bears S.61°W., 9 lks. mkd: T20S R7W S35 BT
A Fir, 20" dia. bears N.40°W. 19 lks. mkd: T20S R7W S26 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - May 1958 - C.S. File 49/93-3

Found - Four orig. BTs. NW BT shows good scar, I do not open. Other BTs now snags, show good scribing. All check distances.
NE orig. BT checks rec. bearing.
SE orig., I find to be S.54°E., rec. S.39°E.
SW orig. BT I find to be S.71°W., rec. S.61°W.
NW orig. BT N.19°W., rec. N.40°W.
I also find stone as recorded at corner.
New BTs- 30" R. Fir bears S.18°W., 16.0 ft. scribed 363 (Martin) T20S R7W S35 BT. (I add CS)
26" R.Fir bears S.31°E., 13.8 ft., bark scribed T20S R7W S36 BT (I add CS)
21" R.Fir bears N.63°E., 9.0 ft., bark scribed T20S R7W S25 363 BT (I add CS)
Set brass cap at corner mkd: S26|S25 T20SR7W County Surveyors
S35|S36 Office 1958

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor 1502, under Group #1392, surveyed Aug. 1989/April 1991 - (DCSO records Vol. 50 Page(s) 19073-4)

The cor. of secs. 25, 26, 35, & 36, perpetuated but not recorded by Leo J. Martin, Registered Land Surveyor No. 363, year unknown, and further perpetuated and recorded by Byron, in 1958, monumented with an iron post, 1¼" diam., firmly set, projecting 14" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees
A decayed fir stump, 14" dia., bears N.54°E., 6 lks., with scribe marks BT visible on overgrowth.
A decayed fir stump, size indeterminate, bears S.61°W., 9 lks., with axe marks visible on decayed blaze.
A fir snag, 20" dia., bears N.21°W., 19 lks., with healed blaze. (Record, N.40°W.)

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of the bearing trees mkd. by Martin
A fir snag, 24" dia., bears N.64°E., 13 lks., with scribe marks 363 T20S R7W S25 BT visible on bark blaze.
A fir snag, 28" dia., bears S.29°E., 21 lks., with scribe marks T20S R7W S36 BT CS visible on open blaze.
A fir snag, 32" dia., bears S.18°W., 24 lks., with healed blaze.
and new bearing trees
A fir, 5" dia. bears N.83°E., 27 lks. mkd. T20S R7W S25 BT
A fir, 5" dia. bears S.51½°E. 22 lks. mkd. T20S R7W S36 BT
A fir, 4" dia., bears S.58°W., 28 lks., mkd. X BT.
A fir, 4" dia., bears N.27½°W., 13½ lks., mkd. X BT.

FD. OK by D. Edwards 6/1998 M130-2
Fd. Ok by H. Christensen 9/1998 M130-35