

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 588)

Set post, 4 ft. long, 4" sq., 2 ft. in the ground, from 1/4 sec. cor., mkd: 1/4 S on W face; from which

A fir, 4" dia., bears N.13°W., 23 lks., mkd: 1/4 S BT.

A fir, 7" dia., bears N.46 1/2°E., 37 lks., mkd: 1/4 S BT.

Wilford N. Haines - For: E.G. Whipple - Dec. 1961 - M21-72 & C.S. File 51/222

Set - 1"x1"x36" T iron from orig. BTs:

Scribed new trees -

32" Fir N.39°W., 23.6 ft.

48" Fir N.11°E., 75.0 ft.

Fd. Ok by D. Edwards 6/1998 - M130-2

Rob Ward - For: Roseburg Resources Co. & Seneca Jones Timber Co. - 3/2001 - M 136-60 & C.S. File 65/36-17 A-L

Found - 1"x1" Haines T iron.

47" D.Fir bears N.39°W. 23.6 ft. bark scribed.

40" D.Fir bears N.15°W. 15.9 ft. healed face.

60" D.Fir bears N.11°E. 75.0 ft. bark scribed.

New BT - 24" D.Fir bears S.34°E. 56.8 ft. blazed, scribed "1/4 S24 BT"