

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor Secs 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 589)

-----  
Set a post, 4 ft. long, 4" square, 24" in the ground, for cor. to secs. 23, 24, 25, & 26, marked T20S S24 on NE R7W S25 on SE, S26 on SW, S23 on NW faces, with 2 notches on S & 1 on E edges; from which  
A fir, 14" dia. bears N.18°E. 18 lks. mkd: T20S R7W S24 BT  
A chittem, 4" dia., bears S.63°E., 12 lks., mkd: T20S R7W S25 BT.  
A fir, 10" dia. bears S.20°W. 27 lks. mkd: T20S R7W S26 BT  
A fir, 14" dia. bears N.2°W., 20 lks. mkd: T20S R7W S23 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - M Godfrey - S.A. Bilow - Nov. 3, 1958 - C.S. File 49/93-5

-----  
Found - (Angle iron & 1" cap) at corner.  
Orig. 14" now 36" fir stump rec. N.18°E., 11.9 ft., should be N.2°E., 11.9 ft., I open & find good scribing "S24".  
Orig. 14" now 31" fir rec. N.2°W., 13.2 ft., should be N.18°W., 13.2 ft.  
Orig. 10" now 24" R.Fir S.20°W., 17.8 ft., shows good scar, I do not open.  
I do not set brass cap at corner.  
New BT - 26" R.Fir bears S.38°E., 17.5 ft. scribed S25 T20S R7W CS BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Stoffel & Stone - Feb. 11, 1964 - C.S. File 49/89-61

-----  
Found - Haines "T" iron & cap.  
36" Fir stump N.2°E., 11.9 ft. scribing visible on old face.  
Fir tree N.18°E., 13.2 ft. uprooted & dead.  
24" Fir S.20°W., 17.8 ft. broken off approx. 6 ft. above ground, top splintered.  
26" Fir S.38°E., 17.5 ft., now dead snag, approx. 50 ft. high.  
New BTs- 14" R.Cedar N.69°W. 48.6 ft. mkd: T20S R7W S23 CS BT  
20" R.Cedar S.26°W. 61.3 ft. mkd: T20S R7W S26 CS BT  
Note - Corner is approx. 40 ft. East of small branch of Panther Creek & 80 ft. West of logging road.  
No trees available East of Line.

continued next page

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor Secs 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1502, surveyed Aug.1989/April 1991 - (DCSO records Vol. 50 Page(s) 19074-5)

-----  
From the cor. of secs. 23, 24, 25, & 26, perpetuated but not recorded by Wilford N. Haines, year unknown, further perpetuated & recorded by Byron, in 1958, & further perpetuated & recorded by Godfrey, in 1964, monumented with "T" shaped iron rod, 1" dia., firmly set, projecting 1" above ground, with washer mkd. WILFORD N HAINES RLS 239 SURVEY PT DRAIN ORE, from which the remains of the original bearing trees:

A sawed fir stump, 36" dia., bears N.3°E., 18 lks., with fragmentary scribe marks visible on opened blaze. (Record, N.18°E.).

A fir snag, 25" dia., bears S.14°W., 27 lks., with healed blaze. (Record, S.20°W.)

A fir snag, 36" dia., bears N.26°W., 16 lks., with healed blaze. (Record, N.2°W., 20 lks.)

and the remains of a bearing tree mkd. by Byron

A fir snag, 29" dia., bears S.38°E., 27 lks., with fragmentary scribe marks visible on partially healed blaze.


and the remains of bearing trees mkd. by Godfrey

A cedar, 13" dia., bears S.25°W., 92 lks., with scribe marks T20S R7W S23 B visible on bark blaze.

A cedar snag, 28" dia., bears N.68°W., 73 lks., with scribe marks W S26 B visible on opened blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground directly atop T iron, with brass cap mkd.



from which new bearing trees

A fir, 12" dia. bears N.89°E. 58 lks. mkd. T20S R7W S24 BT

A hemlock, 6" dia., bears S.20°E., 48 lks., mkd. T20S R7W S25 BT.

An alder, 10" dia., bears N.20°W., 30 lks., mkd. T20S R7W S23 BT on bark.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Fd. Ok by R. Ward, March 2001 - M136-60 & C.S. File 65/36-17B