

PRIMARY CORNER DESCRIPTION Witness Corner to 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 588)

-----  
Set sandstone, 30x14x10" 22" in the ground for witness cor. to ¼ sec. cor. marked ¼ S WC on N face. The ¼ sec. cor. is situated in Smith River, 45 lks., E of the witness cor. from which witness corner  
A Fir, 24" dia., bears N.89°W., 52 lks., mkd: ¼ S W C BT.  
A Fir, 24" dia., bears S.26°E., 50 lks., mkd: ¼ S W C BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy Co. Surveyor - Vernon Tracy - Clete Putnam - Feb/March 1962 - C.S. File 49/89-31

-----  
Found - Fir stump, now 40", S.26°W. (instead of S.26°E.) 33.0 ft., recently opened, good scribing "¼S BT" visible on old faces facing to NE.  
Did not find NW BT or corner rock.  
Corner lies on left (West) bank of Smith River approx 10 ft. from present edge of water.  
Set - Iron pipe with brass cap mkd:  
County Surveyors T20S R7W 30 ft.  
Office 1962 WC¼ S25/S36 E to cor.  
New BTs- 7" D.Fir N.87°W., 45.2 ft. mkd: WC ¼ S25 CS BT.  
9" D.Fir S.55°W., 33.7 ft. mkd: WC ¼ S36 CS BT.

Fd. Ok by H. Christensen, 9/1998 - M130-35

Rob Ward - For: Roseburg Resources Co. & Seneca Jones Timber Co. - 3/2001 - M 136-60 & C.S. File 65/36-17 A-L

-----  
Found - 1962 2½" DCSO brass cap, WC, West 30' from true corner which falls in the Smith River.  
17" D.Fir bears N.87°W., 45.2 ft. healed face.  
23" D.Fir bears S.55°W., 33.7 ft. healed face.  
New BTs- 18" Twin Alder bears N.59°E., 91.6 ft., bark scribed X WC ¼ S25 BT.  
18" Alder bears S.85¼°E., 74.8 ft., bark scribed X WC ¼ S36 BT.