

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 25

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Wilford N. Haines - For: E.G. Whipple - Dec. 1961 - M21-72 & C.S. File 51/222

-----  
Set - 1"x1"x36" T iron  
Scribed new trees -  
    40" Fir S.1°30'E., 47.7 ft.  
    36" Fir S.36°30'E., 65.3 ft.

See M136-60 for calculated position of center 1/4  
Note: This information added 4/23/2007 DCSO - JC

Harvey Christensen - For: Seneca Jones Timber Co. - 2/2007 - M152-66

-----  
Set - 5/8"x30" rebar with 2.5' AC stamped "2006 LS 2603" 0.1 ft above grade.  
    11" R.Alder, N.48°E., 14.4 ft. bark scribed "C¼ S25 BT"  
    14" R.Alder, N.47°W., 9.7 ft. bark scribed "C¼ S25 BT"  
    10" R.Alder, S.42°W., 15.2 ft. bark scribed "C¼ S25 BT"  
    12" R.Alder, S.60°E., 30.5 ft. bark scribed "C¼ S25 BT"  
    6' steel post 0.5' east  
Found - 1" "T" iron w/o brass cap (Haines) 0.6 ft. above grade, S.86°55'38"E., 30.2 ft.  
    2, 5' stumps capped  
Set - 6' steel post 1.8' north  
Found - RP to C¼, 1" "T" iron w/o brass cap (Haines) 0.2 ft. above grade.  
    N.59°25'46"W., 3.8 ft.  
    N.89°22'05"E., 26.9 ft (measured between Haines monuments) [26.9' to RP (Haines Rec.)]  
Set - 6' steel post 1.8' North.