

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 589-90)

-----  
Set sandstone, 24x14x8" 18" in the ground for the 1/4 sec. cor. marked 1/4 on N face; from which

A fir, 8" dia., bears North, 25 lks., mkd: 1/4 S BT.

A dogwood, 4" dia., bears S.57°E., 44 lks., mkd: 1/4 S BT.

-----  
Wilford N. Haines - For: E.G. Whipple - Dec. 1961 - M21-72 & C.S. File 51/222

-----  
Set - 1"x1"x36" T iron 1.2 ft. East of 1/4 rock

There was felled & bucked trees all around this corner.

-----  
Rob Ward - For: Roseburg Resources Co. & Seneca Jones Timber Co. - 3/2001 - M 136-60 & C.S. File 65/36-17 A-L

-----  
Found - Orig. stone w/visible 1/4.

1"x1" Haines T iron bears East 1.2' from stone

25"x3' D.Fir stump bears North 19.6 ft. (16.5' rec.) No visible marks.

New - 30" D.Fir bears S.86 1/2°W. 29.7' blazed, scribed "1/4 S25 BT"

18" D.Fir bears S.67 3/4°E. 17.1' blazed, scribed "1/4 S25 BT"

18" Alder bears N.13°W. 3.5' bark scribed "1/4 S24 BT"