TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Thos. E. Todd under Contract No. 574 dated May 19, 1891 - (DCSO recs. Vol. 2 Page(s) 591)

Set sandstone, 20x14x6" 16" in the ground for the ¼ sec. cor. marked ¼ on N face; from which
A fir, 48" dia., bears N.26°E., 83 lks., mkd: ¼ S BT.
A maple, 4" dia., bears S.45°E., 4 lks., mkd: ¼ S BT.
A small ledge of sandstone 6 lks. S which I mark cross (x) WC

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - May 1958 - C.S. File 49/20-4

Found - Orig. W C chiseled "+ W C" on sandstone ledge.
Find stone that checks size of orig. corner stone out of ground at corner. I do not find any chiseled marks on corner stone nor any trace of orig. BTs.
Set brass cap at corner mkd: ¼ S 13 / S 24 T20S R7W County Surveyors Office 1958
New BTs- 12" R.Fir bears N.43½°E., 20.0 ft., mkd: ¼ S13 CS BT
7" R.Fir bears S.55°E., 26.4 ft., mkd: ¼ S24 CS BT

Rob Ward - 3/2001 - C.S. File 65/36-22

Found - 2½" Douglas Co. brass cap properly mkd.
12" D.Fir S.53½°E., 26.0' healed face.
New - 14" Hemlock bears N.85½°W., 17.2' blazed, scribed "¼ S13 BT"
18" D.Fir bears N.16½°W., 38.4' blazed, scribed "¼ S13 BT"
16" R.Cedar bears S.2¾°W. 19.1' scribed "¼ S24 BT"
Steel post adjacent to corner. All BTs have red painted bands & faces plus yellow BT tag.