

PRIMARY CORNER DESCRIPTION SE. Cor. Sec. 36 (Tsp. Cor.)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 681)

Set post for corner to Tps. 20 & 21 S., Rgs. 6 & 7 W., from which

- An Alder 16" dia., bears N.45°W., 25 lks.
- An Alder 14" dia., bears S.67°W., 29 lks.
- A V.Maple 6" dia., bears S.61°E., 40 lks.
- A V.Maple 7" dia., bears N.43°E., 34 lks.

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 553-54)

Cor. to T20S, Rs. 6 & 7 W., which I found gone, but witness trees standing. Re-established the same by setting post, 6" dia., 4 ft. long, 24" in ground, mkd. T20S S31 on NE.; T21S R7W on S. face; R7W S36 on NW. face; from which old witness trees bear:

- An Alder 20" dia., bears N.45°W., 25 lks. dist. mkd. T20S R7W S36 BT.
 - A Vine Maple 7" dia., bears S.61°E., 40 lks. dist. mkd. T21S R6W S6 BT.
 - A Vine Maple 8" dia., bears N.43°E., 4 lks. dist. mkd. T21S R6W S31 BT.
- Found no bearing tree to the SW.

GLO survey by Thos. E. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 568)

I go to the SE. cor. of T20S R7W, which is a post, 4" sq., firmly set in the ground mkd. T20S S31 on NE.; R6W S6 on SE.; T21S S1 on SW.; R7W S36 on NW. faces, with 6 notches on each edge; from which

- An Alder 16" dia., bears N.45°W., 25 lks. dist. mkd. T20S R7W S36 BT.
- A V.Maple 6" dia., bears S.6°E., 18 lks. dist. (Not S.61°E., 40 lks.) mkd. T21S R6W S6 BT.
- An Alder 14" dia., bears S.67°W., 29 lks. dist. (lying down) mkd. T21S R7W S1 BT.
- A V.Maple 7" dia., bears N.43°E., 24 lks. dist. (Not 34 lks.) mkd. T20S R6W S31 BT.

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23

Found - Orig. BT, a Vine Maple N.43°E., 15.8 ft.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION SE. Cor. for S. 36 (Tsp. Cor.)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Set angle iron at point for corner, from which
44" Fir, N.57°W., 91.9 ft.
X in rock cliff, S.68°W., 95.7 ft.
60" Fir N.41°30'E., 20.1 ft. (had XXXI carved in)

Douglas Co. Surveyors Office - Gary L. Langlitz; Peter Earle
July 15, 1974 - C.S. File 57/2-2

Found - Haines "T" Iron with copper washer attached in good condition.
44" Fir now a stump, bears N.57°W., 91.9 ft., bark scribed "T22S R7W S36 BT" We rescribe to read T20S instead of T22S.
60" Fir now a stump, bears N.41°30'E., 20.1 ft., bark scribed SXXXI BT.
"X" chiseled in vertical sandstone face with copper washer nailed to rock above "X", bears S.68°W., 95.7 ft.

Both BT stumps have been treated with preservative, bark removed except for scribed portion, and metal capped. This corner lies approx. 30 ft. East of Smith River in an area normally flooded in periods of high water. The 44" stump and "X" are located on the West side of Smith River.

Harvey Christensen, survey for Seneca Jones Timber Co.
Sept. 1998 - M130-35

Found - Haines "T" post 0.3 ft. below ground, flood area.
-44" D.Fir, N.57°W., 91.9 ft., 7 ft. stump w/tin cap, bark scribed.
-60" D.Fir, N41.5°E., 20.1 ft. 7 ft. stump w/tin cap, bark scribed.
-Copper washer, S.68°W., 95.7 ft. "X" eroded out of vertical sand stone.
Set 5 ft. steel post 1 ft. West.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22624-5

The cor. of T20S Rs. 6 & 7 W, perpetuated by Haines, in 1956, from original evidence no longer in existence, monumented with a "T" shaped iron rod, ¾" dia., firmly set, flush with the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of accessories mkd by Haines
A sawed fir stump, 58" dia., bears N.42¼°E., 20.1 ft., with scribe marks XXX1 BT visible on the bark. cont.

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE. Cor. Sec. 36 (Tsp. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

An X chiseled on a rock face bears S.68°W., 95.7 ft., with a brass disk mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE nailed 8 ins. above the X.

A sawed fir stump, 42" dia., bears N.57¼°W., 91.1 ft., with scribe marks T20S R7W S36 BT visible on the bark.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T 20 S
R7W R6W
S 36|S 31
S 1
T21S R7W
2009

from which

An alder, 17" dia., bears S.74½°E., 38.9 ft., mkd. T21S R7W S1 BT in the bark.

A fir, 19" dia., bears N.56½°W., 125.0 ft., mkd. T20S R7W S36 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located 55.0 ft. East of the South Fork of Smith River, 30 ft. wide, course N.5°W.