

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E 1/4 Cor. Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 581)

Set a post, 4 ft. long, 4" square, 2 ft. in the ground, for 1/4 sec. cor. mkd. 1/4 S. on W. face; from which -
A Fir, 20" dia. bears N.21°E., 17 lks. dist.
A Fir, 20" dia. bears N.48°W., 36 lks. dist.

Searched for, not fd 1/1962 C.S. File 49/89-13 DCSO Milo Godfrey

Harvey Christensen, survey for Seneca Jones Timber Co. Sept. 1998 - M130-35

1/4 Corner was set at record distance intersection from the original 1891 GLO corner bearing trees (stumps). They were recovered with no scribing remaining but at near record distance from the original West 1/4 corner of Section 31, T20S R6W and with a good pattern.

Bearing trees found -
23" D.Fir, N.5°E., 11.2 ft. (rec. N.21°E., 17 lks.)
hollow stump, no scribing.
24" D.Fir, N.54°E., 23.7 ft. (rec. N.48°W., 36 lks.)
hollow stump, no scribing.
Set - 5/8" x 30" rebar w/yellow plastic cap mkd. "LS 2603"
New Accessories -
12" D.Fir, S.13°E., 30.4 ft. blazed and scribed "X BT"
10" Cascara, N.51°E., 26.9 ft. blazed and scribed "X BT"
7" D.Fir, S.87°W., 24.2 ft. blazed & scribed "1/4 S36 BT"
8" D.Fir, N.55°W., 32.6 ft. blazed & scribed "1/4 S36 BT"
5 ft. steel post set 1 ft. north