

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31 only, T20-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 547)

Set post for corner to secs. 25, 30, 31 & 36; from which
A Fir 24" dia., bears N.37½°E., 19 lks.
A Fir 24" dia., bears S.56°E., 22 lks.
A Fir 24" dia., bears S.34°W., 75 lks.
A Maple 10" dia., bears N.14°W., 24 lks.

GLO Resurvey by Thos. Todd, under contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 582-83)

The old cor. to secs. 30 & 31, R6W, where I find the post decayed. Set a sandstone 24x16x8 ins., 18" in the ground mkd. with 1 notch on S. and 5 notches on N. faces; from which
A Fir 24" dia., bears N.37½°E., 19 lks. dist. mkd. T20S R6W S30 BT.
A Fir 24" dia., bears S.56°E., 22 lks. dist. mkd. T20S R6W S31 BT.
A Fir 24" dia., bears S.34°W., 75 lks. dist. mkd. T20S R7W S36 BT.
A Maple 10" dia., bears N.14°W., 24 lks. dist. mkd. T20S R7W S25 BT.

Wilford N. Haines, #239 - (Found and reported by M.E. Godfrey, Deputy, Feb. 1962 - C.S. File 49/89-30 (See Haines map M 21-72))

Found - Sandstone rock, 16x8x12 ins., above ground, firmly set. 1 notch on S. side; "+" & "CC" on top. Haines' T Iron alongside.
42" Fir, N.30°E., 16.6 ft. (not N.37½°E. 12.5 ft.) previously opened, scribing "S30" visible on old face. Tree in good condition.
42" Fir S.63°E., 12.6 ft. (not S.56°E. 14.5 ft.) shows very good scar. Didn't open. Tree in good condition.
38" Fir stump S.37°W., 47.5 ft. (not S.34°W. 49.5 ft.) Chopped open & found bottom of old scar with axe marks, just blow top of stump. Apparently scribing all on log which was gone.
No trace of Maple to NW.

(Cont. Next Page)

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 700203

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31 only, T20-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Weyerhaeuser Co. Wm. L. Wilt, Land Agent - Jan. 9, 1963 -
C.S. File 53/102-6

Found - Sandstone 16x8x12 ins. well above ground & firmly
set. On top side is mkd. "+" & "CC", also Haines
"T" iron.

24" Fir N.37½°E., 12.5 ft., now 42" (green) face
open, shows scribing.

24" Fir S.56°E., 14.5 ft., now 42" Fir (green)
healed face, unopened.

24" Fir S.34°W., 49.5 ft., now 38" Fir stump, shows
bottom old face.

10" Maple N.14°W., 15.8 ft., no trace found.

Marked the following trees with "W" nails and plate:

42" Fir, N.31°E., 15.0 ft. (Orig. BT)

42" Fir, S.67°E., 10.8 ft. (Orig. BT)

38" Fir stump S.37°W., 46.0 ft. (Orig. BT)

4" Chinquapin N.66°W., 13.0 ft.

Fd. T Iron, Stone & 3 BTs - June 1991 by D. Peel - M 113-45