

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 25 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 583)

-----  
Set sandstone 20x18x8 ins., 15" in the ground, for ¼ sec. cor., mkd. ¼ on W. face; from which  
A Fir 20" dia., bears S.42°E., 8 lks. dist. mkd. ¼ S BT.  
A Fir 24" dia., bears S.83°W., 49 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C Putnam, crew - Jan. 1962 - C.S. File 49/89-26

-----  
Found - Haines "T" Iron and cap at corner. Also, 1/2" galv. Iron pipe.  
Old Fir stump S.83°W., 29.0 ft., instead of 32.3 ft.  
Found good scribing, part of "4" and a "B".  
Old Fir stump S.42°E., 5.3 ft., old face burned away, had been previously opened.  
Did not find sandstone called for in old notes.  
8" Fir S.67°E., 30.3 ft. scribed ¼ S BT.  
8" double Maple, East 18.9 ft. scribed in bark "¼S BT"  
Did not set brass cap.  
New BT - 4" D.Fir S.58°W., 23.3 ft. mkd. ¼ S25 CS BT.  
No other trees available.

Fd. T-Iron and 4 BTs, June 1991 by D. Peel - M 113-45

Rob Ward - For: Roseburg Resources Co. & Seneca Jones Timber Co. - 3/2001 - M 136-60 & C.S. File 65/36-17 A-L

-----  
Found - 1"x1" Haines T iron with ½" gal. iron pipe alongside 19"x5' D.Fir stump bears S.85°W. 28.7' vis. scribing 20"x4'D.Fir stump S.47°E., 5.6' burned face w/axe work.  
23" D.Fir bears S.56¼°W., 23.0' healed face.  
14" Maple stump bears N.89 3/4°E., 18.8' no visible marks.  
New BT - 16" Maple bears N.49°w., 13.1 ft. blazed, scribed "¼ S25 BT"

Harvey Christensen - For: Seneca Jones Timber Co. - 2/2007 - M152-66

-----  
Found - 1" "T" iron w/o brass cap (Haines) 0.8 ft above grade. BTs as per M136-60  
Set - 6' steel post 0.5' west.