

TOWNSHIP 20 RANGE 07 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 586)

Set post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face; from which
A Fir 10" dia., bears East, 36 lks. dist., mkd. ¼ S BT.
A Fir 20" dia., bears N.67°W., 64 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C. Putnam, crew - Feb. 1962 - C.S. File 49/89-32

Found - 20" Fir, now 40", N.67°W., 42.2 ft. (slope dist.)
Had been chopped open previously & good scribing
"S" is visible on small portion of old face.
10" Fir now 32", East, 23.8 ft. (slope dist.) Old
scars barely visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 20 S R 7 W
¼ S 13 |
1962

Blaze & scribe one new tree:
16" D.Fir S.16°W., 15.1 ft. mkd. ¼ S13 DCS BT.

BLM Resurvey by Harvey E. Wofford and Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16077)

(Found corner report only)
The ¼ sec.cor. of sec. 13 only, perpetuated and recorded by Godfrey in 1962, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1962, from which the original bearing trees:

A Fir 32" dia., bears East, 33 lks. dist. with healed blaze. (Rec. 36 lks.)
A Fir 45" dia., bears N.67°W., 59 lks. dist. with healed blaze. (Rec. 64 lks.)
and a bearing tree mkd. by Godfrey:
A Fir 16" dia., bears S.16°W., 16 lks. dist. with healed blaze.