

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 315)

Fir, 8" dia. for ¼ sec. cor., marked ¼ S on W face, from which
Maple 6" dia., bears N.80°W., 45 lks. dist. mkd. ¼ S BT
Cedar 30" dia., bears S.78°E., 12 lks. dist. mkd. ¼ S BT

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11333)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

¼ S 31

1950

from which
A Fir 28" dia., bears N.57°E., 108 lks. dist. mkd. ¼ S31 BT.
A Hemlock 24" dia., bears S.24°E., 59 lks. dist., mkd. ¼ S31 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16709)

The ¼ sec. cor. of sec. 31 only, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap mkd. ¼ S 31

1950

from which bearing trees mkd. in 1950
A Fir 33" dia., bears N.57°E., 108 lks. dist., with healed blaze.
A Hemlock 28" dia., bears S.24°E., 59 lks. dist., with fragmentary scribe marks visible on burned blaze.
Rescribed ¼ S31 BT on new blaze.
Set a 5 ft. steel fence post alongside the iron post.