

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only, T20-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12468)

Point for the ¼ sec. cor. of sec. 25 only, at midpoint on the E. bdy. of sec. 25.

Set an iron post 3 ft. long, 1" dia., 28" in the ground with brass cap mkd: ¼ S 25 |
1954

from which

A Fir 25" dia., bears S.13°W., 10 lks. mkd. ¼ S25 BT.

A Fir 19" dia., bears N.85°45'W., 24 lks. mkd. ¼ S25 BT.

BLM Remonumentation of corner by Wm. Glenn; C. monument White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16710-11)

The ¼ sec. cor., monumented with an iron post 1" dia., firmly set, projecting 10" above ground with brass cap mkd. in 1954 from which bearing trees mkd. in 1954:

A Fir 28" dia., bears S.13°W., 10 lks. dist. with healed blaze.

A Fir 21" dia., bears N.85 ¾°W., 24 lks. dist. with healed blaze.

Set a 5 ft. steel fence post alongside the iron pipe.

Survey by Les Roberts - For: International Paper Co. - March 1993 - C.S. File 63/149-11 and M 116-60

Found - 1954 GLO brass cap set firmly in the ground.
22" Fir N.85°W., 15.8 ft., scar visible. (1954 rec. N.85 ¾°W., 15.8 ft.)
28" Fir S.12°W., 6.6 ft., scar visible. (1954 BT, rec. S.13°W., 6.6 ft.)

Set 72" alum. post land monument survey sign attached to, beside brass cap. Painted all bearing trees red.

Cor. lies on W. slope about 50 ft. S. of the NW. corner of sec. 30.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22963-4)

The ¼ Cor. Sec. 25 only, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100279

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only, T20-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

A fir, 31" dia., bears S.13°W., 6.6 ft., with a healed blaze.

A fir high stump, 23" dia., bears N.85¾°W., 15.8 ft., with a healed blaze.

and a new bearing tree

A fir, 7" dia., bears N.61½°W., 24.5 ft., mkd. ¼ S25 BT.

A steel and an aluminum fence post are alongside the cor.

The, cor. of secs. 19 & 30 on the W. bdy. of T20S R8W bears N.0°32'44"W., 49.59 ft.

Fd. BC & accessories as per 2011 BLM rec by D. Edwards
12/2017 - C.S. File 65/98-2