

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100339

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25, T20-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 353)

At point of intersection, I set a Cedar post, for closing corner to secs. 24 & 25, 4 ft. long, 4" sq., 24" in the ground, marked CC T20S S24 on N.; S25 on S.; CC R9W on W. faces, with 2 notches on S. and 4 notches on N. faces; from which

An Alder 24" dia., bears S.80°E., 30 lks. dist. mkd. T20S R9W S24 & 25 CC BT.

An Alder 18" dia., bears N.46°W., 60 lks. dist. mkd. T20S R9W S24 BT.

A Maple 48" dia., bears S.64°W., 106 lks. dist. mkd. T20S R9W S25 BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12468)

Point for the closing cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S	T 20 S
CC S 24	S 19
S 25	
R 9 W	R 8 W
1954	

from which

A Maple 25" dia., bears N.25°W., 33 lks. dist. mkd. T20S R9W S24 CC BT.

A Maple 105" dia., bears West, 172 lks. dist. mkd. T20S R9W S25 CC BT.

(The ¼ sec. cor. sec. 19, T20S R8W bears N.0°42'E., 0.78 chs.)

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16711-12)

The closing cor., monumented with an iron post 2" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1954,

from which the remains of the bearing trees mkd. in 1954:

A root hole bears N.25°W., 33 lks. dist. with a down Maple alongside, 18" dia., with fragmentary scribe marks visible on decayed blaze.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25, T20-9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

and new bearing trees:
A Maple 25" dia., bears S.22°W., 153 lks. dist. mkd. T20S R9W S25 CC BT.
A Maple 39" dia., bears N.74°W., 253½ lks. dist. mkd. T20S R9W S24 CC BT.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 (added 12/31/2014) - (DCSO records Vol. 58 Page(s) 23080)

The closing cor. of secs. 24 & 25, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd. from which the remains of a BT mkd by Glenn, et. al., in 1967

A Roothole bears S.22°W., 101.0 ft. with a down decayed maple, 26" dia., lying alongside, no marks visible.

and new BTs

An alder, 16" dia., bears S.72¼°W., 31.9 ft., mkd: T20S R9W S25 CC BT on bark, with a Mag nail on the left side center.

A fir, 17" dia., bears N.70¼°W., 59.1 ft., mkd: T20S R9W S24 CC BT.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22967)

The closing cor. of secs. 24 and 25, on the W. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with a brass cap mkd. and accessories as described in the 2006-09 official survey by Forkner.

BLM retracement by Joseph M. Mannix, Cadastral Surveyor under Group No. 2500, Admin. file No. 1306, surveyed May 2013 - (DCSO records Vol. 58 Page(s) 23070 & Survey plat 2014-1)

The closing cor. of secs. 24 & 25, on the E. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 10 ins, above ground, with a brass cap mkd. from which the bearing trees mkd. by Forkner in 2006-09

An alder, 20" dia., bears S.72¼°W., 31.9 ft., with scribe marks T20S R9W S25 CC BT visible on bark.

A fir, 22" dia., bears N.70¼°W., 59.1 ft., with a healed blaze.

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100339

PRIMARY CORNER DESCRIPTION C C for Secs. 24 & 25, T20-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From the corner
S.89°59'04"W., 90 ft., Smith River Road, asphalt surface,
20 ft. wide, bears N.50°E. and S.50°W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 9/1/2021 (filed 3/21/2023) - C.S. File 67/55-48

Reported as found ok
Found as described 2013 BLM retracement.
Add BLM tie to W¼ 19, T20S R8W N0°34'18"E., 51.35 ft.