

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 317-18)

-----  
Set post 6" dia., 4 ft. long, with marked stone, 12" in ground for cor. to secs. 12, 13, 7 and 18, marked T20S S7 on NE.; R8W S18 on SE.; R9W S13 on SW.; S12 on NW. faces, with 4 notches on S. and 2 on N. edges; from which  
Hemlock 7" dia., bears N.68°E., 5 lks. dist. mkd. T20S R8W S7 BT.  
Dogwood 6" dia., bears S.63°E., 30 lks. dist. mkd. T20S R8W S18 BT.  
Hemlock 8" dia., bears S.46°W., 5 lks. dist. mkd. T20S R9W S13 BT.  
Maple 20" dia., bears N.65°W., 36 lks. dist. mkd. T20S R9W S12 BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12350)

-----  
The cor. of secs. 7 & 18, determined at record bearing and distances from the original bearing trees:  
A shattered Hemlock stump 13" dia., bears N.68°E., 5 lks. dist. marked with portions of scribe marks.  
A Dogwood 10" dia., bears S.63°E., 30 lks. dist. marked with a healed blaze.  
A Hemlock 16" dia., bears S.46°W., 5 lks. dist. with marks T20S R9W S13 uncovered.  
A Maple 38" dia., bears N.65°W., 36 lks. dist., marked with a healed blaze.

At the corner point  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd: \*T 20 S

T 20 S\*  
R 9 W\* S 7  
S 13\* S 18  
\* R 8 W

1954

from which a new bearing tree  
A Hemlock 20" dia., bears N.84°E., 49 lks. dist. mkd. T20S R8W S7 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16715)

-----  
The cor. of secs. 7 & 18 only, monumented with an iron post 2" dia., firmly set, projecting 4" above ground with brass cap mkd. in 1954, from which the remains of the original bearing trees:

A root hole, bears S.63°E., 30 lks. dist. with a down Dogwood alongside, 10" dia., with healed blaze.

A Hemlock stump 18" dia., bears S.56°W., 5 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Rec. S.46°W.)

A root hole, bears N.65°W., 36 lks. dist., with a down Maple alongside, 38" dia., with healed blaze.

and a bearing tree marked in 1954:

A Hemlock 23" dia., bears N.84°E., 49 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a new bearing tree:

A Hemlock 40" dia., bears S.39½°E., 110 lks. dist. mkd. T20S R8W S18 BT.

Set a 5 ft. steel fence post alongside the iron post.

Fd. OK, Dec. 1986 by L. Roberts - M 103-36

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22896)

-----  
The cor. of secs. 7 & 18 only, on the W. bdy. of T20S R8W determined at record dist. from the remains of a bearing tree marked by Tillman, et al., in 1953-54

A decayed hemlock snag, leaning N 42" dia., bears N.80°E., 32.3 ft., no marks visible. (Record, N.84°E.)

and at record bearing and from the remains of a BT mkd. by Glenn, et al., in 1967

A decayed hemlock stump, 46" dia., bears S.39½°E., 72.6 ft., no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2½" dia., 24" in the ground, with bronze cap mkd.

	T20S
T20S	S 7
R9W	S 18
S 13	R8W
	2011

from which

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A white fir, 13" dia., bears N.62¼°E., 31.0 ft., mkd. T20S  
R8W S7 BT.

A hemlock, 10" dia., bears S.71°E., 28.6 ft., mkd. T20S  
R8W S18 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post. Drive an aluminum post alongside the cor., which falls in a small slide area 90 ft. S. of an overgrown graveled road, 10 ft. wide, bears N.70°W. and S.70°E.