

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, (West)

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 318-19)

Set post 6" dia., 4 ft. long, in ground 12" with marked stone for cor. to secs. 6, 7, 1 & 12, marked T20S S6 on NE.; R8W S7 on SE.; R9W S12 on SW.; S1 on NW. face, with 5 notches on S. & 1 on N. edges; from which


- Fir 40" dia., bears N.45°E., 71 lks. mkd. T20S R8W S6 BT.
- Fir 48" dia., bears S.62°E., 30 lks. mkd. T20S R8W S7 BT.
- Fir 36" dia., bears S.57°W., 32 lks. mkd. T20S R9W S12 BT.
- Fir 10" dia., bears N.66°W., 18 lks. mkd. T20S R9W S1 BT.

GLO Resurvey Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug 1953/Sept 1954 - (DCSO recs Vol 29 Pg 12352)

The cor. of secs. 6 & 7, determined at record bearing and distance from the original bearing trees:

- A Fir snag 70" dia., bears N.45°E., 71 lks. dist. with partial scribe marks visible on bark.
- A Fir snag 76" dia., bears S.62°E., 30 lks. dist. with partial scribe marks visible on bark.
- A Fir snag 50" dia., bears S.57°W., 32 lks. dist., mkd. T20S R9W S12 BT on bark.
- A partially rotted Fir stump 12" dia., bears N.66°W., 18 lks. dist., with no remaining marks.

At the corner point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:



from which new bearing trees:

- A Hemlock 8" dia., bears N.23½°E., 47 lks. dist., mkd. T20S R8W S6 BT.
- A Hemlock 13" dia., bears S.22½°E., 22 lks. dist., mkd. T20S R8W S7 BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21753)

The cor. of secs. 6 and 7 only, monumented with an iron post, 2" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd. continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which the remains of the original bearing trees
A decayed fir stump, 66" dia., bears N.45°E., 44.8 ft.,
with a healed blaze. (Record, 46.9 ft.)
A decayed fir stump, 72" dia., bears S.62°E., 24.0 ft., no
marks visible. (Record, 19.8 ft.)
A fir stump, 50" dia., bears S.57°W., 21.1 ft., no marks
visible.
and the remains of a BT mkd. by Tillman, et al., in 1953-54
A hemlock stump, size indeterminate, bears N.23½°E., 31.0
ft., no marks visible.
and new bearing trees
A fir, 9" dia. bears N.18½°E., 16.2 ft mkd. T20S R8W S6 BT
A fir, 7" dia. bears S.29°E., 9.8 ft., mkd. T20S R8W S7 BT
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center.

Ronald L Rice - For: Oxbow Timber 1 LLC - Nov. 2015 - M170-30

Found - GLO brass cap dated 1953 w/following accessories:
Rotted 66" fir stump bears N.45°E., 44.8', healed
face.
Rotted 72" fir stump bears S.62°E., 24.0', no marks.
50" metal capped fir stump bears S.57°W., 21.1', no
marks.
13" D.Fir bears N.18½°E., 16.2', healed face.
12" D.Fir bears S.29°E., 9.8', healed face.
Steel post adjacent to corner.

Fd. as per rec. by T.Hostetter 1/2020 - C.S. File 65/105-7