

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 12 only, T20-9

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Pgs 362-63)

 For closing cor. of secs. 1 & 12, I marked, at point of intersection, a Vine Maple 4" dia., T20S S1 on N.; R9W S12 on S.; and CC on W. sides, with 1 notch on N. and 5 notches on S. sides; from which
 A Fir 12" dia., bears N.55½°W., 37 lks. dist. mkd. T20S R9W S1 BT.
 A Fir 42" dia., bears S.51°W., 54 lks. dist., mkd. T20S R9W S12 BT.
 A Fir 24" dia., bears N.33½°E., 38 lks. dist. mkd. T20S R9W CC S1 & 12 BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12478-79)

 (58.85 chs.)
 The original closing cor. of secs. 1 and 12, determined from the remaining original bearing trees, as follows:
 A Fir 40" dia., bears N.23°E., 38 lks. dist., with illegible scribe marks visible on bark blaze. (Rec. brg. N.33½°E.)
 An uprooted Fir 20" dia., marked T20S R9W on bark blaze, the stump hole of which bears N.33°W., 37 lks. dist. (Rec. brg. N.55½°W.)

(59.06 chs.) (N.88°56'E.)
 Point for the closing cor. of secs. 1 and 12.
 Set an iron post 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S	T 20 S
CC $\frac{S 1}{S 12}$	S 6
R 9 W	R 8 W
	1953

from which
 A Hemlock 10" dia., bears N.51°W., 78 lks. dist. mkd. T20S R9W S1 CC BT.
 A Cedar 20" dia., bears S.38°W., 27 lks. dist. mkd. T20S R9W S12 CC BT.
 (From this point, the ¼ sec. cor. on the W. bdy. of sec. 6, T20S R8W, bears N.0°57'E., 1.73 chs.)

Tony Hostetter - For: Roseburg Resources - Jan. 2020 - C.S. File 65/105-7

 Found - 1953 BLM brass cap, from which:

Continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 100638

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 12 only, T20-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

10" Hemlock stump, 1953 BT no marks, bears; N.51°W.,
51.5 ft to center.
New BTs- 14" Fir, marked "X", BT tag, bears; S.73°33'E., 31.6
ft to spike.
9" Fir, marked "X", BT tag, bears; S.16°34'E., 5.7
ft to spike.
14" Fir, marked "X", BT tag, bears; N.63°16'W., 3.1
ft to spike.