

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 319)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for ¼ sec. cor., marked ¼ S on W. face; from which
Fir 18" dia., bears S.19°E., 14 lks. dist., mkd. ¼ S BT.
Fir 12" dia., bears S.70°W., 36 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12353)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: | ¼ S 6
1953
from which
A Hemlock 10" dia., bears N.76½°E., 44 lks. mkd. ¼ S6 BT.
A Fir 43" dia., bears S.18½°E., 12 lks., mkd. ¼ S6 BT.

Tony Hostetter - For: Roseburg Resources - Jan. 2020 - C.S. File 65/105-7

Found - 1953 BLM brass cap, from which:
22" Hemlock, 1953 BT, part of BT tag, bears; N.76½°E., 29.0 ft to center.
New BTs- 12" Fir, marked "X", BT tag, bears; S.68°W., 11.7 ft to spike.
8" Fir, marked "X", BT tag, bears; N.21°W., 8.1 ft to spike.

Fd BC & 3 BTs 9/2020 by J Estabrook M177-40
Lat & long per Garmin Etrex hand held GPS-NOT SURVEY GRADE
N: 43°51'22.0 W: 123d42'12.8"