

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 490)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked 1/4 S on N face; from which
Maple, 6" dia., bears S.7°W., 24 lks., mkd: 1/4 S BT.
Fir, 40" dia., bears N.48°E., 18 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11359)

Point for the 1/4 sec. cor. of secs. 30 & 31, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
1/4 S 30
 S 31
 1950

from which
A fir, 38" dia., bears N.53°45'W., 12 lks., mkd: 1/4 S30 BT.
A fir, 54" dia., bears S.53°45'E., 21 lks., mkd: 1/4 S31 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16746)

The 1/4 sec. cor. of secs. 30 & 31, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.
from which the remains of the BTs marked in 1950
A sawed fir stump, 60" dia., bears N.53 3/4°E., 12 lks., with healed blaze.
A burned fir, 50" dia., bears S.53 3/4°E., 21 lks., with healed blaze.
Set a 5 ft. steel fence post alongside the iron post.

Ron Rice - For: Oxbow Timber 1 LLC - Feb. 2014 - M167-42

Found - 2 1/2" GLO brass cap dated 1950 with the following accessories
60" Fir stump bears N.53 3/4°W., 7.9' - rotted face
50" Fir stump bears S.53 3/4°E., 13.9' - rotted face
New BTS- 19" D.Fir bears N.13°W., 11.4' - blazed, scribed 1/4 S30 BT
15" D.Fir bears N.22°E. 10.5' - blazed, scribed X BT
20" D.Fir bears N.66°E., 22.1' - blazed, scribed 1/4 S30 BT

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

28" D.Fir bears S.13°W., 19.3' - blazed, scribed ¼
S31 BT
Steel post adjacent to corner