

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 492)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face, raised mound of stone alongside. No witness trees.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11363)

-----  
Point for the ¼ sec. cor. of secs. 19 & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼  $\frac{S\ 19}{S\ 30}$   
1950

from which

A fir, 20" dia., bears N.68°45'W., 24 lks., mkd: ¼ S19 BT.

A fir, 18" dia., bears S.57½°E., 37 lks., mkd: ¼ S30 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16747-8)

-----  
The ¼ sec. cor. of secs. 19 & 30, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the BTs marks in 1950

A fir, 28" dia., bears N.68¾°W., 24 lks., with healed blaze.

A root hole, bears S.57½°E., 37 lks., with a down fir alongside, 24" dia., with scribe marks ¼ S30 BT visible on open blaze.

and a new BT

A fir, 33" dia., bears S.19¾°W., 73½ lks., mkd: ¼ S30 BT.

Set a 5 ft. steel fence post alongside the iron post.

Survey by Les Roberts - For: International Paper Co. - March 1993 - C.S. File 63/149-11 and M 116-60

-----  
Found - 1950 GLO brass cap set firmly in the ground.  
28" Fir stump, N.68°W., 15.8' (scar vis) 1950 BT.  
Rec. N.68¾°W., 15.8'.

34" Fir stump, S.20°W., 48.5' (scar vis) Rec. S.19¾°W., 48.5'

New - 8" fir, S.53°W., 16.2' (scribed & painted red)  
continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

10" Fir, N.41°W., 30.8' (scribed & painted red)  
72" alum. post, with land survey sign attached to,  
beside brass cap.  
Note - Corner lies on West slope about 300' West of gravel  
logging road.

---

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22962-3)  
-----  
The ¼ sec. cor. of secs. 19 and 30, monumented with an iron post, 1" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd.  
from which the remains of a BT mkd. by Tillman in 1950  
A fir stump, 19" dia., bears N.68¾°W., 15.8 ft., with a healed blaze.  
and the bearing trees mkd. by Roberts, PLS No. 1039, in 1993  
A fir, 17" dia., bears S.49½°W., 15.0 ft., with a healed blaze.  
A fir, 15" dia., bears N.43¼°W., 29.7 ft., with a healed blaze.  
An aluminum fence post is alongside the cor.  
From the corner  
W., 390 ft., creek, 3 ft. wide, course S.  
E., 270 ft., graveled road, 15 ft. wide, bears N. and S.  
Latitude: 43°48'22.51"N. Longitude: 123°41'21.86"W.  
NAD 1983 (CORS 96)

---

2