

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 496)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which Hemlock, 10" dia., bears N.54°E., 8 lks., mkd: ¼ S BT.
Hemlock, 10" dia., bears S.40°W., 15 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12387)

Point for the ¼ sec. cor. of secs. 7 & 18, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ $\frac{S \ 7}{S \ 18}$
1954

from which

A hemlock, 13" dia., bears N.15°E., 29 lks., mkd: ¼ S7 BT.
A hemlock, 20" dia., bears S.60¼°E., 38 lks. mkd: ¼ S18 BT

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16751)

The ¼ sec. cor. of secs. 7 & 18, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

and the remains of the BT marked in 1954

A hemlock 16" dia. bears N.15°E. 29 lks. with healed blaze
A hemlock, 22" dia., bears S.60¼°E., 38 lks., with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

Fd. Ok by Les Roberts, Dec. 1986 - M103-36-1(A)

Les Roberts, LS 1039 - May 5, 1989 - C.S. File 63/85-14

Found - 1954 GLO brass cap laying on cut-bank of new dirt logging road. Both 1954 BTs have been destroyed.
Set - Reset 1954 GLO brass cap from M103-36 traverse points. Brass cap buried 6" below surface of dirt road. Buried purple magnetic marker under pipe.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

New BTs- 30" Hemlock, N.29°E., 88.2 ft. (scribed/painted red)
32" Fir, S.50°E., 48.6 ft. (scribed/painted red)
Distances are measured to 6" spike driven into center of tree.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2670, Surveyed May 2012/June 2013 - (DCSO records Vol. 58 Pages 23049-50)

The 1/4 sec. cor. of secS.7 and 18, perpetuated by Roberts, in 1989, monumented with an iron post, 1" dia., firmly set, with top 12" below the surface of the ground, with a brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Roberts
A hemlock stump, 37" dia., bears N.27°E., 86.9 ft., with scribe marks ¼ S7 BT visible on partially opened blaze.

A fir stump, 34" dia., bears S.50½°E., 48.4 ft., with scribe marks ¼ S18 visible on open blaze.

and bearing trees mkd. by person(s) unknown

A fir, 9" dia., bears N.51½°E., 6.5 ft., with a healed blaze.

A fir, 11" dia., bears S.23½°W., 21.1 ft., mkd. ¼ S17 BT. and new reference monuments

A rebar, 30" long, 5/8" dia., driven 30" in the ground bears S.51°31'40"W., 30.31 ft., with an aluminum cap mkd. RM ¼ S18 30.3 ft. TO COR 2013, and an arrow pointing to the cor.

A rebar, 30" long, 5/8" dia., driven 30" in the ground bears N.31°05'03"W., 23.85 ft., with an aluminum cap mkd. RM ¼ S7 23.9 ft. TO COR 2013, and an arrow pointing to the cor.

Corner is located in a dirt road, 10 ft. wide, bears E. & W. NAD83 (2011)

Latitude: 43°50'05.66"N. Longitude: 123°41'21.12"W.