

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & S. 31, T19-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 460)

-----  
Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for qr. sec. cor., marked ¼ S on N. face; from which  
Fir 12" dia., bears N.15°E., 69 lks. dist. mkd. ¼ S BT.  
Fir 10" dia., bears S.37°W., 50 lks. dist. mkd. ¼ S BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 505-06)

-----  
Failed to find the corners on the N. bdy. of T20S R8W, except those on the N. bdy. of sec. 1. After diligent search I fail to find any other of the original marks of this line or any marks of lines coming in from the South. (This excerpt was taken from Vol. 2 Pg. 501)

Set post 4 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which  
A Fir 14" dia., bears S.56°W., 40 lks. dist. mkd. ¼ S BT.  
A Fir 20" dia., bears N.14½°W., 35 lks. dist. mkd. ¼ S BT

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12356)

-----  
The ¼ sec. cor. of secs. 6 and 31, determined at record bearing and distance from the original bearing tree:

A Fir 26" dia., bears S.56°W., 40 lks. dist. mkd. with a healed blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 24" in the ground, with brass cap mkd: ¼  $\frac{S\ 31}{S\ 6}$   
1954

from which a new bearing tree:

A Fir 38" dia., bears N.42°W., 89 lks. dist. mkd. ¼ S31 BT

Corner report by Wayne Donovan, LS #2553 - May 19, 1993 - C.S. File 63/153-57

-----  
Found - 1954 GLO brass cap out of ground, Reset from existing bearing tree.

32" Fir bears S.56°W., 26.4 ft., healed face.

1954 BT, blow down.

(Cont. Next Page)

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & S. 31, T19-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 9" Fir bears N.64°W., 18.2 ft., blazed and scribed  
"¼ S31 BT"  
5" Fir bears S.85°E., 20.5 ft., blazed and scribed  
"¼ S6 BT"  
9" Hemlock bears N.10°W., 26.8 ft., blazed and  
scribed "¼ S31 BT"

BLM dependent resurvey by Edith M Forkner & Jason A  
Lightbown, Cadastral Surveyors, under Group #2820, surveyed  
Feb./June 2016 - (DCSO records Vol. 59 Page(s) 23529)

-----  
The ¼ sec. cor. of secs. 6 and 31, perpetuated by Donovan, in  
1993, monumented with an iron post, 1" dia., firmly set, in  
a mound of stone, 2 ft. base, 2 ft. high, top projecting 10"  
above the mound, with a brass cap (properly) mkd.  
from which the remains of a BT mkd. by Collier in 1891  
A fir, 39" dia., bears S.56°W., 26.4 ft., with a healed  
blaze.  
and the bearing trees mkd. by Donovan  
A fir, 12" dia., bears S.88½°E., 20.6 ft., with a healed  
blaze.  
A hemlock, 19" dia., bears N.15°W., 27.3 ft., with a  
healed blaze.  
A fir, 15" dia., bears N.64½°W., 18.3 ft., with a healed  
blaze.