

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Remonumentation by Wm. Glenn; C. Albert White & James E. Jelley, Cadastral Surveyors, under Group #'s 350 & 635, surveyed April/May 1967 - (DCSO rec. Vol. 43 Page(s) 16708)

 The Sec. cor., monumented with an iron post, 2" dia., firmly set, projecting 5" above ground, with brass cap mkd. in 1945, from which the remains of the bearing trees mkd. in 1945:

A burned Fir snag 25" dia., bears N.68½°E., 23½ lks., with no marks remaining on burned blaze. (Rec. N.67°E., 21 lks.) Rescribed "T20S R8W S32 BT" on new blaze.

A burned Fir snag 12" dia., bears S.36½°E., 128 lks., no marks remaining on burned blaze.

A burned Fir snag 27" dia., bears S.10°W., 176 lks., no marks remaining on burned blaze.

and new bearing trees:

A Fir stump 22" dia., bears S.11½°E., 67 lks., mkd. T21S R8W S5 BT.

A burned Fir snag, 25" dia., bears S.22°W., 116 lks. mkd. T21S R8W S6 BT.

A burned Fir snag 17" dia., bears N.17½°W., 55 lks. mkd. T20S R8W S31 BT.

Set a 5 ft. steel fence post alongside the iron post.

 Gary Smithers - Jan. 2002 - C.S. File 65/42-10

Found - 1945 brass cap on iron pipe firmly set with steel fence post driven alongside the brass cap.

25" burnt & rotting Fir stump, N.68½°E., 23½ lks., with old tag & visible scribes.

15" burnt & rotting Fir stump, S.36½°E., 128 lks., with visible scribes.

30" burnt & rotting Fir stump, S.10°W., 176 lks., with visible scribes.

22" burnt & rotting Fir stump, S.11½°E., 67 lks., with visible scribes & old tag.

25" burnt & rotting Fir snag, S.22°W., 116 lks., with visible scribes.

17" burnt & rotting Fir snag, N.17½°W., 55 lks., with visible scribes & old tag.

New BTs- 9" D.Fir N.11°W., 2.9 ft. to spike driven in side center, mkd: "T20 R8 S31 BT" with BT tag.

9" D.Fir N.19°E., 13.5 ft. to spike driven in side center, mkd: "T20 R8 S32 BT" with BT tag.

15" D.Fir S.79°E., 18.1 ft. to spike driven in side center, mkd: "T21 R8 S5 BT" with BT tag.

9" D.Fir S.2°W., 15.8 ft. to spike driven in side center, mkd: "T21 R8 S5 BT" with BT tag.

Cont.

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6 T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. BC & BTs; & steel post adjacent to corner by R. Rice
2/2014 - M167-42

Fd ok 10/2019 - R. Quimby - C.S. File 65/104-22