TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 489)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face; from which
Fir, 6" dia., bears N.72°W., 18 lks., mkd: ¼ S BT.
Fir, 4" dia., bears S.68°E., 24 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11357)

Point for the ¼ sec. cor. of secs. 31 & 32, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 31|S 32
1950

from which
A fir, 30" dia., bears S.2°45'E., 83 lks., mkd: ¼ S32 BT.
A fir, 60" dia., bears N.68°W., 92 lks., mkd: ¼ S31 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16744-5)

The ¼ sec. cor. of secs. 31 & 32, monumented with an iron post, 1" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.
from which the remains of the BTs marked in 1950
A burned fir snag, 32" dia., bears S.2¾°E., 83 lks., with scribe marks S32 visible on burned blaze.
and a new BT
A burned & sawed hemlock stump, 18" dia., bears S.77°W., 79 lks., mkd: ¼ S31 BT.
Set a 6 ft. steel fence post alongside the iron post.

Ron Rice - For: Oxbow Timber 1 LLC - Feb. 2014 - M167-42

Found - 2½" GLO brass cap dated 1950 with the following accessories:
32" Fir snag bears N.2¾°E., 54.8' - scribing visible
New BTs- 13 D.Fir bears N.41°W., 8.3' - blazed, scribed X BT
19 D.Fir bears N.24°W., 34.6' - blazed, scribed ¼ S31 BT
17" D.Fir bears N.10°E., 22.4' - blazed, scribed ¼ S32 BT

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

15" D.Fir bears S.42°E., 16.0' - blazed, scribed ¼ S32 BT
Steel post adjacent to corner