

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 489)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 29, 30, 31, & 32, mkd. T 20S S 29 on NE, R 8W S 32 on SE, S 31 on SW, S 30 on NW face, with 5 notches on E & 1 on S edge; from which

- Fir, 6" dia., bears N.85°E., 15 lks., mkd: T20S R8W S29 BT
- Fir, 10" dia., bears S.58°E., 15 lks. mkd: T20S R8W S32 BT
- Fir, 6" dia., bears S.64°W., 26 lks., mkd: T20S R8W S31 BT
- Fir, 6" dia., bears N.44°W., 36 lks., mkd: T20S R8W S30 BT

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11357-8)

The cor. of secs. 29, 30, 31, & 32, located at the point of intersection of orig. blazed line, duly identified.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked

T20S	R8W
S 30	S 29
S 31	S 32
1950	

from which new BTs

- A fir, 36" dia. bears N.47°E. 38 lks. mkd: T20S R8W S29 BT
- A cedar, 20" dia., bears S.74°E., 30 lks., mkd: T20S R8W S32 BT.
- A fir, 60" dia., bears S.71°W., 33 lks., mkd: T20S R8W S31 BT.
- A fir, 30" dia., bears N.38°45'W., 67 lks., mkd: T20S R8W S30 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jolley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16745)

The corner of secs. 29, 30, 31 & 32, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground with brass cap (properly) mkd.

from which the remains of the BTs marked in 1950

- A burned fir, 43" dia., bears N.47°E., 38 lks. with healed blaze.
- A burned cedar, 25" dia., bears S.74°E., 28½ lks., no marks visible on burned blaze. (Rec. 30 lks.) Rescribed T20S R8W S32 BT on new blaze.
- A burned fir, 60" dia., bears S.71°W., 33 lks., with healed blaze.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned fir, 40" dia,. bears N.38¾°W., 67 lks., with
healed blaze.
Set a 5 ft. steel fence post alongside the iron post.

Ron Rice - For: Oxbow Timber 1 LLC - Feb. 2014 - M167-42

Found - 2½" GLO brass cap dated 1950 with the following
accessories:

- 43" Fir stump bears N.47°E., 25.1' - healed face
- 25" Cedar stump bears S.74°E., 18.8' - no scribing
- 60" Fir stump bears (S).71°W., 21.8' - healed face
- 40" Fir stump bears N.38¾°W., 44.2' - healed face

- New BTs-
- 16" D.Fir bears N.85°W., 16.8' - blazed, scribed
T20S R8W S30 BT
 - 20" D.Fir bears N.42°E., 15.9' - blazed, scribed
T20S R8W S29 BT
 - 12" D.Fir bears S.80°E., 18.7' - blazed, scribed
T20S R8W S32 BT
 - 20" D.Fir bears S.16°W., 42.4' - blazed, scribed
T20S R8W S31 BT
- Steel post adjacent to corner

Fd. BC & BTs per M167-42 by R Rice - Nov. 2015 - C.S. 65/92-2