

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 491)

-----

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 19, 20, 29, & 30, mkd. T 20S S 20 on NE, R 8W S 29 on SE, S 30 on SW, S 19 on NW face, with 2 notches on S & 5 on E edge; from which

- Fir, 10" dia., bears N.53°E., 20 lks. mkd: T20S R8W S20 BT
- Fir, 10" dia., bears S.55°E., 25 lks. mkd: T20S R8W S29 BT
- Fir, 8" dia., bears S.42°W., 21 lks., mkd: T20S R8W S30 BT
- Fir, 6" dia., bears N.34°W., 14 lks., mkd: T20S R8W S19 BT

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11361)

-----

The cor. of secs. 19, 20, 29, & 30, determined at the rec. dist. from the orig. NE BT & the rec. bearing & dist. from the orig. SE, SW, & NW BTs as follows:

- A fir stump, 12" dia., bears N.50°E., 20 lks., with blaze decayed. (Rec. bearing N.53°E.,)
- A fir, 14" dia., bears S.55°E., 25 lks. with blaze healed.
- A stump hole, bears S.42°W., 21 lks.
- A fir stub, 6" dia., bears N.34°W., 14 lks., with the scribe marks BT S19 visible on the partly overgrown blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked

T20S	R8W
<u>S 19</u>	<u>S 20</u>
S 30	S 29
1950	

from which new BTs

- A fir, 14" dia., bears N.10°E., 24 lks., mkd: T20S R8W S20 BT.
- A fir, 26" dia., bears S.71½°W., 49 lks., mkd: T20S R8W S30 BT.
- A fir, 16" dia., bears N.36½°W., 35 lks., mkd: T20S R8W S19 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16746-7)

-----

The corner of secs. 19, 20, 29 & 30, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground with brass cap (properly) mkd.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of the orig. BTs  
A sawed fir stump, 10" dia., bears S.55°E., 25 lks., no marks remaining on burned blaze.  
from which the remains of the BTs marked in 1950  
A sawed fir stump, 10" dia., bears N.10°E., 24 lks., no marks remaining on burned blaze. Rescribed T20S R8W S20 BT on new blaze.  
A sawed fir stump, 30" dia., bears S.71½°W., 49 lks., with healed blaze.  
A sawed fir stump, 10" dia., bears N.36½°W., 35 lks., with healed blaze.  
Set a 5 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21773)

-----  
The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd.  
from which the remains of BTs mkd. by Tillman in 1950  
A fir snag, 13" dia., bears N.10°E., 15.8 ft., with scribe marks R8W S20 BT visible on burned partially healed blaze.  
A fir stump, 26" dia., bears S.71½°W., 32.3 ft., no marks visible.  
A decayed fir stump, 10" dia., bears N.36½°W., 23.1 ft., with scribe mark T visible on open blaze.  
and new bearing trees  
A fir, 17" dia., bears N.56°E., 20.4 ft., mkd. T20S R8W S20 BT.  
A fir, 8" dia., bears S.67½°E., 26.6 ft., mkd. T20S R8W S29 BT.  
A fir, 11" dia., bears S.74°W., 23.0 ft., mkd. T20S R8W S30 BT.  
A fir, 11" dia., bears N.27½°W., 36.9 ft., mkd. T20S R8W S19 BT.  
There is a steel fence post alongside the corner.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22962)

-----  
The cor. of secs. 19, 20, 29, & 30, monumented with an iron post, 2" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd. continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of the BTs mkd. by Tillman in 1950  
A fir snag, 13" dia., bears N.10°E., 15.8 ft., with illegible scribe marks visible on burned blaze.  
A fir stump, 18" dia., bears S.71½°W., 32.3 ft., with a decayed blaze.  
A decayed fir stump, 18" dia., bears N.36½°W., 23.1 ft., no marks visible.  
and the remains of the bearing trees mkd. by Graham in 2005  
A fir, 20" dia., bears N.26¼°E., 20.4 ft., with a healed blaze and a Mag Nail on the right side center. (Record, N.56°E.)  
A fir, 9" dia., bears S.66½°E., 26.3 ft., with a healed blaze and a Mag Nail on the right side center. (Record, S.67½°E., 26.6 ft.)  
A fir, 14" dia., bears S.74°W., 23.0 ft., with a healed blaze and a Mag Nail on the right side center.  
A fir, 13" dia., bears N.27½°W., 35.4 ft., with a healed blaze and a Mag Nail on the right side center. (Record, 36.9 ft.)  
A steel fence post is alongside the cor.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23189)

-----  
The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd.  
from which the remains of the bearing trees mkd. by Tillman in 1950  
A decayed fir snag, 14" dia., bears N.10°E., 15.8 ft., with no marks visible on burned partially healed blaze and illegible scribe marks alongside and above blaze.  
A fir stump, 17" dia., bears S.71½°W., 32.3 ft., with no marks visible on open decayed blaze.  
A decayed fir stump, size indeterminate, bears N.36½°W., 23.1 ft., with scribe marks S B and other illegible scribe marks visible on detached pieces of blaze.  
and the bearing trees mkd. by Graham in 2005  
A fir, 21" dia., bears N.56°E., 20.4 ft., with a healed blaze and a Mag Nail at the base on the right side center. (Record, N.26¼°E.)  
A fir, 9" dia., bears S.66½°E., 26.3 ft., with a healed blaze & a Mag Nail at the base on the right side center  
A fir, 14" dia., bears S.74°W., 23.0 ft., with a healed blaze & a Mag Nail at the base on the right side center  
continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 13" dia., bears N.27½°W., 35.4 ft., with a healed blaze & a Mag Nail at the base on the right side center  
A steel fence post is alongside the cor.