

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Pages 494-5)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 7, 8, 17, & 18, mkd. T 20S S 8 on NE, R 8W S 17 on SE, S 18 on SW, S 7 on NW face, with 4 notches on S & 5 on E edge; from which

Fir, 24" dia., bears S.72°E., 30 lks. mkd: T20S R8W S17 BT
Fir, 24" dia., bears S.2°W., 63 lks., mkd: T20S R8W S18 BT
Fir, 30" dia., bears N.36°E., 128 lks. mkd: T20S R8W S8 BT
Alder, 12" dia. bears N.59°W., 74 lks. mkd: T20S R8W S7 BT

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12385-6)

Point for the cor. of secs. 7, 8, 17, & 18, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 16" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked:

T20S	R8W
S 7	S 8
S 18	S 17
1954	

from which

A cedar, 16" dia., bears N.14½°E., 85 lks., mkd: T20S R8W S8 BT.
A fir, 40" dia., bears S.4°E., 50 lks., mkd: T20S R8W S17 BT.
A fir, 46" dia., bears S.88°W., 84 lks., mkd: T20S R8W S18 BT.
A maple, 20" dia., bears N.13¼°W., 56 lks., mkd: T20S R8W S7 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16750)

The corner of secs. 7, 8, 17, & 18 monumented with an iron post, 2" dia., firmly set, projecting 10" above ground with brass cap (properly) mkd.

from which the remains of the BTs marked in 1954

A root hole bears N.14½°E., 85 lks., with a down cedar alongside, 18" dia., with healed blaze.
A sawed fir stump, 42" dia., bears S.4°E., 50 lks., with healed blaze.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A sawed fir stump, 44" dia., bears S.88°W., 76 lks., no marks remaining on burned blaze. (Rec. 84 lks.) Rescribed T20S R8W S18 BT on new blaze.

A root hole, bears N.13¼°W., 56 lks., with a down maple alongside 22" dia., with scribe marks T20S R8W S7 BT visible on open blaze.

and a new BT

A sawed cedar stump, 28" dia., bears N.43°W., 73½ lks., mkd: T20S R8W S7 BT.

Set a 5 ft. steel fence post alongside the iron post.

Robert Dean, LS 1808 & Wm. J. Ruppert, LS 866 - For: International Paper Co. - 3/30/1983 - M93-80 & C.S. 58/204(N)

Found - 1¼" galv. iron pipe, loose & leaning in slide area, (I reset to vertical with 2½" GLO brass cap marked: T20S R8W S7 S8 S18 S17 1954) from which:

- 36" fir stump with BT visible in rotted face bears S.4°6'E., 31.9 ft. (rec. S.4°E., 33.0 ft.)
- 35" fir stump bears S.87°52'W., 50.8 ft. (rec. S.88°W., 55.44 ft.)
- 28" cedar stump with: T20S R8W S7 BT visible bears N.41°49'W., 48.2 ft. (rec. per 1967 BLM remonumentation: N.43°W., 48.51 ft.)

New BTs-

- 7" D.Fir, scribed T20S R8W S8 BT, bears N.71°30'E., 24.4 ft.
- 9" D.Fir, scribed T20S R17W S8 BT, bears S.60°20'E., 18.75 ft.
- 7" D.Fir, scribed T20S R8W S18 BT, bears S.21°19'W., 16.5 ft.
- 8" D.Fir, scribed T20S R8W S7 BT, bears N.52°43'W., 24.4 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2670, Surveyed May 2012/June 2013 - (DCSO records Vol. 58 Pages 23047)

The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Tillman, et al., in 1953-54

- A burnt fir stump, 21" dia., bears S.4°E., 33.0 ft., with a healed blaze.
- A decayed fir stump, 37" dia., bears S.88°W., 50.2 ft., no marks visible.

and the bearing trees mkd. by Dean, PLS No. 1808, in 1983

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 12" dia., bears N.71½°E., 24.4 ft., with a healed blaze.
A fir, 22" dia., bears S.60¼°E., 18.8 ft., with a healed blaze.
A fir, 12" dia., bears S.21¼°W., 16.5 ft., with a healed blaze.
A fir, 16" dia., bears N.52 34°W., 24.4 ft., with a healed blaze. (typed as per BLM rec: 1983 rec. N.52°43'W. - JC DCSO 5/5/2014)