

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 498)

Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on W face, raised mound of stone, 18" high, 3½ ft. sq. at base.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12390-1)

Point for the ¼ sec. cor. of secs. 5 & 6, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 6 | S 5
1954

from which

A cedar, 11" dia., bears S.26°E., 83 lks., mkd: ¼ S5 BT.

A fir, 40" dia., bears N.6°W., 84 lks., mkd: ¼ S6 BT.

Ronald L Rice - For: Oxbow Timber 1 LLC - Nov. 2015 - M170-30

Found - GLO brass cap dated 1954 with the following accessories:

Record 40" fir bearing N.6°W., down out of position
New BTs- 6" D.Fir bears N.60°W., 1.8', blazed scribed ¼ S6 BT
12" D.Fir bears N.23°E. 13.5' blazed scribed ¼ S5 BT
14" D.Fir bears S.25°E. 21.5' blazed scribed ¼ S5 BT
16" D.Fir bears S.2°W. 30.6' blazed scribed ¼ S6 BT
Steel post adjacent to corner.