

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 495)

-----  
Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for gr. sec. cor. marked ¼ S on N face; from which Hemlock, 18" dia., bears N.20°E., 39 lks., mkd: ¼ S BT. Maple, 20" dia., bears S.26°E., 34 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12386)

-----  
Point for the ¼ sec. cor. of secs. 8 & 17, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:  
¼  $\frac{S \ 8}{S \ 17}$   
1954

from which  
A fir, 18" dia., bears North, 32 lks., mkd: ¼ S8 BT.  
A fir, 27" dia., bears S.35°E., 47 lks., mkd: ¼ S17 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16750-1)

-----  
The ¼ sec. cor. of secs. 8 & 17, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.  
and the remains of the BT marked in 1954  
A fir, 21" dia., bears North, 32 lks., with healed blaze.  
A fir, 33" dia., bears S.35°E., 47 lks. with healed blaze.  
Set a 5 ft. steel fence post alongside the iron post.