

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 497)

 Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked ¼ S on N face; from which
 Cedar, 30" dia., bears S.62°E., 52 lks., mkd: ¼ S BT.
 Cedar, 20" dia., bears N.17°W., 16 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A Tillman, Raymond M. Bicknell, Han W. Thielsen & Joseph S. Gawron, Cadastral Engineers, under Group No. 305 surveyed Aug. 1953 thru Sept. 1954 - (DCSO recs. Vol. 29 Page(s) 12389)

 The ¼ sec. cor. of secs. 5 & 8, determined at rec. bearing & dist. from the remaining orig. BT:

A cedar, 40" dia., bears S.62°E., 52 lks., marked with a rotted blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

$$\frac{1}{4} \begin{array}{c} S \ 5 \\ S \ 8 \\ 1954 \end{array}$$

from which new BTs

A cedar, 33" dia., bears N.59°W., 70 lks., mkd: ¼ S5 BT.

A fir, 25" dia., bears S.54¼°W., 72 lks., mkd: ¼ S8 BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21775)

 The ¼ sec. cor. of secs. 5 and 8, monumented with an iron post, 1" dia., firmly set, projecting 2" above the ground, with brass cap. (properly) mkd.

from which the remains of bearing trees mkd. by Tillman, et al., in 1953-54

A fir snag, 23" dia., bears S.54¼°W., 47.5 ft., with scribe marks ¼ S8 BT visible on partially healed blaze.

A burned cedar stump, 31" dia., bears N.59°W., 46.2 ft., no marks visible.

and new bearing trees

A fir, 16" dia., bears S.17°E., 12.2 ft., mkd. ¼ S8 BT.

A fir, 9" dia., bears N.7½°W., 23.0 ft., mkd. ¼ S5 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ronald L. Rice, Ward NW - Witness Jason Collier - April 9, 2012 - C.S. File 65/76-37 & C.S. File 65/81-12 (3/2014)

Found - 2½ BLM brass cap on iron pipe, dated 1954
A fir snag, 23" dia., bears S.54¼°W., 47.5 ft., with scribe marks ¼ S8 BT visible on partially healed blaze. No change
A burned cedar stump, 31" dia., bears N.59°W., 46.2 ft., no marks visible. No change
A fir, 16" dia., bears S.17°E., 12.2 ft., mkd. ¼ S8 BT. Now 19" with healed face
A fir, 9" dia., bears N.7½°W., 23.0 ft., mkd. ¼ S5 BT. Now 9" with healed face
New - 23" D.Fir bears N.74°E., 12.1 ft. blazed, scribed, ¼ S5 BT
Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.
Compass Declination 16° East

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2670, Surveyed May 2012/June 2013 - (DCSO records Vol. 58 Pages 23048-9)

The 1/4 sec. cor. of secS.5 and 8, perpetuated by Rice, in 2012, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Tillman, et al., in 1953-54

A decayed fir stump, 21" dia., bears S.54¼°W., 44.7 ft., with scribe marks ¼ S8 BT visible on partially healed blaze. (Record, 47.5 ft.)

A decayed cedar stump, 30" dia., bears N.59°W., 42.7 ft., no marks visible. (Record, 46.2 ft.)

and the bearing trees mkd. by Graham in 2005

A fir, 20" dia., bears S.17°E., 12.2 ft., with a healed blaze.

A fir, 9" dia., bears N.9½°W., 23.0 ft., with a healed blaze. (Record, N.7½°W.)

and a bearing tree mkd. by Rice

A fir, 24" dia., bears N.74°E., 12.1 ft., with scribe marks ¼ S5 BT visible on partially healed blaze.

At S.89°47' 12" E., at:

40 ft., Herb Creek road, gravel surfaced, 10 ft. wide, bears N.15°E. and S.5°W., in curve.

90 ft., Herb Creek, 27 ft. wide, course S.5°W.