

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 461)

-----  
Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for ¼ sec. cor. marked ¼ S on N. face; from which  
    Fir 20" dia., bears N.45°E., 29 lks. dist. mkd. ¼ S BT.  
    Fir 20" dia., bears S.25°E., 40 lks. dist. mkd. ¼ S BT.

GLO survey by C.M. Collier, Deputy Surveyor, under Group #580 dated June 23, 1891 - (DCSO records Vol. 2 Page(s) 505)

-----  
Failed to find the corners on the N. bdy. of T20S R8W, except those on the N. bdy. of sec. 1. After diligent search I fail to find any other of the original marks of this line or any marks of lines coming in from the South. (This excerpt was taken from Vol. 2 Pg. 501)

Set post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face; from which  
    A Fir 14" dia., bears N.53°W., 13 lks. dist., mkd. ¼ S BT.  
    A Fir 14" dia., bears S.73°E., 13 lks. dist., mkd. ¼ S BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12354)

-----  
The ¼ sec. cor., determined at record bearing from the original bearing trees:  
    A Fir 19" dia., bears N.53°W., 15 lks. dist., marked with a healed blaze. (Rec. distance, 13 lks.)  
    A Fir 10" dia., bears S.73°E., 15 lks. dist. with no marks remaining on blaze. (Record, A Fir, 14" dia., 13 lks.)  
At the corner point  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:  
                            ¼  $\frac{S\ 32}{S\ 5}$   
                                            1954  
from which new bearing trees:  
    A Fir 13" dia., bears N.2½°E., 36 lks. dist. mkd. ¼ S32 BT.  
    A Cedar 18" dia., bears S.60°E., 64 lks. dist. mkd. ¼ S5 BT.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & S. 32, T19-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ron Rice - for: Oxbow Timber 1 LLC - Oct. 2014 - M168-56

-----

Found - 1954 GLO brass cap with the following accessories:  
19" D.Fir stump bears N.53°W., 9.9' - Healed face  
10" Rotted D.Fir stump bears S.73°E. 9.9' - No marks  
40" D.Fir stump bears N.2½°E., 23.4' - Healed face  
26" Cedar bears S.60°E., 42.2' - Rotted open face  
New BTs- 17" Hemlock bears N.37°W., 12.0' - blazed, scribed ¼  
          S32 BT  
          18" D.Fir bears N.37°E., 27.9' - blazed, scribed ¼  
          S32 BT  
          13" Alder bears S.74°W., 17.5' - blazed, scribed ¼  
          S5 BT  
          15" D.Fir bears S.18°E., 14.3' - blazed, scribed ¼  
          S5 BT.  
Steel post adjacent to corner

Fd as per M168-56 12/2016 by R. Rice - C.S. file 65/96-2