

PRIMARY CORNER DESCRIPTION Sec Cor for 32 & 33; 4 & 5, T21-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 452)

-----  
Set post 6" dia., 4 ft. long, with marked stone, 12" in ground for cor. to secs. 4, 5, 32 & 33, marked T20S S33 on NE.; R8W S4 on SE.; T21S S5 on SW.; S32 on NW. faces, with 2 notches on W. & 4 notches on E. edge; from which  
Cedar 20" dia., bears N.85°E., 43 lks. mkd T20S R8W S33 BT  
Cedar 36" dia., bears S.82°E., 43 lks. mkd. T21S R8W S4 BT  
Cedar 20" dia., bears S.75°W., 6 lks. mkd. T21S R8W S5 BT  
Hemlock 20" dia bears N.19°W., 74 lks mkd. T20S R8W S32 BT

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11391-92)

-----  
The cor. of secs. 4, 5, 32 & 33, the locus of which is determined by reference to the record measurements from the old NE., m SE., and SW bearing trees.  
At the corner point  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:  
T 20 S R 8 W  
S 32 \* S 33  
S 5 \* S 4  
T 21 S  
1945

from which  
A Cedar 22" dia., bears N.89½°E., 43 lks. with face of old blaze decayed. I re-blaze and re-mark this old bearing tree T20S R8W S33 BT.  
A Cedar 40" dia., bears S.75°E., 43 lks., with face of old blaze decayed. (Old BT)  
A Cedar stump 30" dia., bears S.62°W., 6 lks. on which no marks remain. (Old BT)  
A Fir 60" dia., bears S.61°E., 66 lks. mkd. T21S R8W S4 BT. (New BT)  
A Fir 60" dia., bears S.41°W., 33 lks., mkd. T21S R8W S5 BT. (New BT)  
A Hemlock 12" dia., bears N.11°W., 107 lks. mkd. T20S R8W S32 BT. (New BT)

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO rec Vol 43 Pg 16707)

-----  
The sec. cor., determined at record bearing and distance from the remains of the original bearing trees: cont. next pg

PRIMARY CORNER DESCRIPTION Sec Cor for 32 & 33; 4 & 5, T21-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A burned Cedar stump, bears S.75°E. 43 lks no marks remaining  
 A burned Cedar stump 8" dia., bears S.62°W., 6 lks. dist.,  
 no marks remaining.  
 and the remains of the bearing trees mkd. in 1945:  
 A burned Fir stump 56" dia., bears S.61°E., 66 lks. dist.,  
 no scribe marks remaining on burned blaze. Rescribed  
 T20S R8W S4 BT on new blaze.  
 At the corner point  
 Set an iron post, 28" long, 2½" dia., 28" in the ground, with  
 brass cap mkd:  
   T 20 S R 8 W  
   S 32\*S 33  
   S 5\*S 4  
   T 21 S R 8 W  
   1967  
 from which new bearing trees:  
 A Cedar stump 40" dia., bears N.¼°E., 111 lks. dist. mkd.  
 T20S R8W S33 BT.  
 A burned Cedar stump 56" dia., bears N.56°W., 174 lks.  
 dist. mkd. T20S R8W S32 BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor  
 under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol.  
 55 Page(s) 21746-7)  
 -----  
 The cor. of secs. 4, 5, 32, and 33, monumented with an iron  
 post, 2½" dia., firmly set, projecting 4" above the ground  
 with brass cap (properly) mkd.  
 from which the remaining original bearing tree  
 A root hole bears S.62°W., 4.0 ft.  
 and the remains of a BT mkd. by Price and Rigby in 1945  
 A burned fir snag, 54" dia., bears S.61°E., 43.6 ft., with  
 scribe marks T21S R8W S visible on open decayed blaze.  
 and the remains of BTs mkd. by Glenn, et al., in 1967  
 A cedar stump, 42" dia., bears N.¼°E., 73.3 ft., with  
 scribe marks T20S R8W S33 BT visible on open decayed  
 blaze.  
 A cedar stump, 47" dia., bears N.56°W., 114.8 ft., with scribe  
 marks T20S R8W S32 BT visible on open decayed blaze.  
 and new bearing trees  
 A fir, 8" dia. bears S.82°E., 30.1 ft. mkd. T21S R8W S4 BT  
 A fir, 14" dia. bears S.½°W., 14.6 ft. mkd. T21S R8W S5 BT  
 A fir, 15" dia bears N.56½°W., 25.2 ft mkd T20S R8W S32 BT  
 No suitable trees to the NE. available.  
 Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)  
 driven at the base right side-center.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 4 & 5, T21-8

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2285, surveyed Aug. 2009/ Feb. 2010 (DCSO records BLM plat 2011 & Vol. 56 Page(s) 22263-65)

-----  
The cor. of sec. 4, 5, 32, and 33, on the N. bdy. of the Tp., remonumented by Price and Rigby in 1945, by Glenn, et. al. in 1967; and rehabilitated by Graham in 2005; monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.

from which the remains of an original BT

A roothole bears S.62°W., 4.0 ft.

and the remain; of a BT mkd. by Price and Rigby

A burned fir snag. 54" dia., bears S.61°E., 43.6 ft., with scribe marks T21S R8W visible on open blaze.

and the remains of the BTs mkd. by Glenn, at al.

A cedar stump. 42" dia., bears N.1/4°E., 73.3 ft., with scribe marks T20S R8W S33 BT visible on open blaze.

A cedar stump. 57" dia., bears N.56°W., 114.8 ft., with scribe marks T20S R8W S32 BT visible on open blaze.

(Record, stump, 47" dia.)

and the BTs mkd. by Graham

A fir, 10" dia. bears S.82°E., 29.7 ft with a healed blaze and a Mag Nail on the right side center. (Rec. 30.1 ft)

A fir, 18" dia., bears S.1/2°W., 14.6 ft., with illegible scribe marks visible on partially healed blaze and a Mag Nail on the right side center.

A fir, 15" dia., bears N.56½°W., 25.2 ft., with a healed blaze end a Mag Nail on the right side center.

Corner is located S., 50 ft. from a drew, drains S.75°E.

No suitable bearing trees within limits in sec. 33.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22956)

-----  
The cor. of secs. 4, 5, 32, & 33, on the S. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, with a brass cap mkd. & accessories as described in the 2009-10 official survey by Forkner, except the fence post alongside has been flattened by a log. Drive an aluminum angle iron, 5 ft. long, alongside the cor.

Fd. BC & BTs; & alum. post adjacent to corner by R. Rice  
2/2014 - M167-42