

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 482)

Set post, 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 28, 29, 32, & 33, mkd. T 20S S 28 on NE, R 8W S 33 on SE, S 32 on SW, S 29 on NW face, with 4 notches on E & 1 on S edge; from which

 Fir, 12" dia., bears N.38°E., 9 lks., mkd: T20S R8W S28 BT
 Fir, 7" dia., bears S.47°E., 7 lks., mkd: T20S R8W S33 BT.
 Fir, 14" dia., bears S.63°W., 29 lks. mkd: T20S R8W S32 BT
 Fir, 7" dia., bears N.47°W., 36 lks., mkd: T20S R8W S29 BT

BLM dependent resurvey by Thomas A. Tillman, under Group # 292 Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Pages 11352-3)

The cor. of secs. 28, 29, 32, & 33, determined at the rec. bearing & dist. from the orig. NE, SE, & SW BTs, as follows:

 A fir, 32" dia., bears N.38°E., 9 lks. plainly blazed & healed.

 An uprooted fir, 12" dia., the stump hole of which bears S.47°E., 7 lks., with the scribe marks BT S33 T visible on the opened blaze.

 A fir 28" dia bears S.63°W. 29 lks plainly blazed & healed

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked

T20S	R8W
<u>S 29</u>	<u>S 28</u>
S 32	S 33
1950	

from which new BTs

 A fir, 16" dia., bears S.65½°E., 35 lks., mkd: T20S R8W S33 BT.

 A fir, 16" dia., bears N.21½°W., 40 lks., mkd: T20S R8W S29 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jolley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16739)

The corner of secs. 28, 29, 32 & 33, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground with brass cap (properly) mkd.

from which the remains of the orig. BTs

 A burned fir, 32" dia., bears N.38°E., 9 lks. with healed blaze.

 A burned fir, 30" dia., bears S.63°W., 29 lks. with healed blaze.

continued next page

TOWNSHIP 20 RANGE 08 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of the BTs marked in 1950
A burned fir, 17" dia., bears S.65½°E., 37 lks. with
healed blaze. (Rec. 35 lks.)
A burned fir, 17" dia., bears N.21½°W., 42 lks., with
healed blaze. (Rec. 40 lks.)
Set a 5 ft. steel fence post alongside the iron post.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22957)

The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2" dia., firmly set, projecting 12 ins. above ground, with a brass cap (properly) mkd.

from which the remains of the original bearing trees
A decayed fir stump, 24" dia., bears N.38°E., 5.9 ft., no marks visible.
A decayed fir stump, 24" dia., bears S.63°W., 19.1 ft., no marks visible.

and the remains of a bearing tree mkd. by Tillman in 1950
A decayed fir snag, 11" dia., bears S.65½°E., 24.4 ft., no marks visible. (Record, 23.1 ft.)

and new bearing trees
A W.Fir, 11" dia., bears N.32°E., 36.7 ft., mkd. T20S R8W S28 BT.
A fir, 19" dia., bears S.47½°E., 29.8 ft., mkd. T20S R8W S33 BT.
A fir, 19" dia., bears S.49½°W., 17.9 ft., mkd. T20S R8W S32 BT.
A W.Fir, 11" dia., bears N.31°W., 12.9 ft., mkd. T20S R8W S29 BT.

A steel fence post is alongside the cor.
Latitude 43°47'30.85" N. Longitude 123°39'00.13"W.
(NAD 1983 (CORS 96))

Fd. GLO BC & accessories per 2011 BLM survey, R Rice 11/2015
- C.S. 65/92-2