

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 28 & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO records Vol. 2 Page(s) 483)

-----  
Set post, 4" dia., 4 ft. long, with marked stone, 12" in ground, for qr. sec. cor. marked 1/4 S on W face; from which Hemlock, 4" dia., bears N.75°W., 17 lks., mkd: 1/4 S BT. Cedar, 6" dia., bears S.18°E., 24 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11354)

-----  
Point for the 1/4 sec. cor. of secs. 28 & 29, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4  
S 29 | S 28  
1950

from which

A fir, 25" dia., bears S.64°E., 74 lks., mkd: 1/4 S28 BT.

A fir, 8" dia., bears N.31°W., 24 lks., mkd: 1/4 S29 BT.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16739)

-----  
The 1/4 sec. cor. of secs. 28 & 29, monumented with an iron post, 1" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.

from which the remains of the BT marked in 1950

A burned fir stump, 9" dia., bears N.31°W., 24 lks., no marks remaining.

and a new BT & a reference monument

A burned fir stump, 35" dia., bears N.42 1/2°E., 151 lks., mkd: 1/4 S28 BT.

An iron post, 28" long, 2 1/2" dia., set 24" in the ground, for a reference monument, bears N.41°W., 58 lks., with brass cap mkd: 1/4 S29 RM 1967 and an arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the iron post.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21766-7)

-----  
The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1" dia., firmly set, 4" below the ground, with brass cap (properly) mkd. continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 28 & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of a bearing tree and a reference monument mkd. by Glenn, et al., in 1967

A burned fir stump, 34" dia., bears N.42½°E., 99.7 ft., with a healed blaze.

An iron post, 2½" dia., firmly set, flush with the ground, bears N.41°W., 38.3 ft., with brass cap mkd. ¼ S29 RM 1967 and an arrow pointing to the corner.

and a new bearing tree

A fir, 10" dia., bears N.51½°E., 56.4 ft., mkd. ¼ S28 BT. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22958-9)

The ¼ sec. cor. of secs. 28 & 29, monumented with an iron post, 1" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd.

from which the remains of a BT mkd. by Tillman in 1950

A decayed burned fir stump, 26" dia., bears S.64°E., 48.8 ft., no marks visible.

and accessories established by Glenn, et al., in 1967

A decayed burned fir stump, 35" dia., bears N.42½°E., 99.7 ft., no marks visible and a Weyerhaeuser tag.

An iron post, 2½" dia., firmly set, projecting 3" above ground, bears N.40°19'56"W., 37.99 ft., with brass cap mkd. ¼ S29 RM 1967 and an arrow pointing to the cor. and with a steel fence post is alongside. (Record, N.41°W., 38.28 ft.)

and a bearing tree mkd. by Graham in 2005

A fir, 12" dia., bears N.51½°E., 56.4 ft., with a healed blaze.

A steel fence post is alongside the cor.

Corner falls on the W. edge of an over grown dirt road, 15 ft. wide, bears N.30°E. and S.25°W.

From the corner

S., 305 ft., knob on the top of a ridge, bears N.50°E. and S.50°W.