

PRIMARY CORNER DESCRIPTION Line Tree - Angle Point

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Thomas A. Tillman, under Group # 292, Surveyed June/Oct. 1950 (DCSO recs Vol. 27 Page 11355)

 A fir, 50" dia., marked with 2 hacks on N & S sides.

BLM remonumentation of Orig. corner points by Wm. W. Glenn, C. Albert White, & James E. Jelley, Cadastral Surveyors, under Group #s 350 & 635, surveyed April & May 1967 (DCSO records Vol. 43 Page(s) 16740)

 Orig. Line tree
 A burned 54" dia., bears S.4°17'W., 29 lks. (from Cor. of secs. 20, 21, 28 & 29) with 2 healed blazes on the north and south faces.
 Set a 5 ft. steel fence post alongside the west reference monument.

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22959)

 The line tree bet. secs. 28 and 29, established by Tillman in 1950, monumented with a decayed fir stump, 49" dia., with no marks visible, recovered by Glenn et. Al., in 1967, described then as a burned fir, 54" dia., with 2 healed blazes on the north and south faces. This now becomes an Angle Point.
 At the corner point
 Saw the line tree stump flush with the surface of the ground on the uphill side and drive an aluminum rod, 14" long, 1/2" dia., 12" in the center of the stump, with aluminum cap mkd.
 AP
 S 29 | S 28
 2011
 (Corner of secs. 20, 21, 28, & 29 bears N.4°11'52"E., 18.14')